



Channel - Lok™

BIN FLOORS & SUPPORTS

Installation & Owner's Manual

MAJOR BIN DIAMETERS

15'	18'	21'
24'	27'	30'
33'	36'	42'
48'	54'	60'
72'	75'	78'
90'	105'	

Sukup Manufacturing Co.

1555 255th Street, Box 677

Sheffield, Iowa, USA 50475-0677

Phone: 641-892-4222

Fax: 641-892-4629

Website: www.sukup.com

E-mail: info@sukup.com

<u>DATE</u>	<u>REVISIONS</u>	<u>PAGES</u>
11/18/2015	Added note on not using sidedraw and sumps at same time	7
11/18/2015	Updated Z-Post & flooring requirements for bins with recirculating devices	12-13, 15
11/18/2015	Updated instructions for using concrete blocks for supports	25
11/18/2016	Updated instructions for supporting floor over conveyor	30-32
11/18/2016	Added instructions for supporting floor planks at splices	33
11/18/2016	Updated notes on floor plank location tables & installation of supports	37
11/18/2016	Added plank location tables for 15'- 36' dia. bins	39-55
04/11/2016	Updated language throughout on supporting ends of planks	
03/11/2016	Added note on installation of flush floor over aeration tunnel(s)	3
03/11/2016	Updated warranty	4
03/11/2016	Added notice on fan use	7
03/11/2016	Added note limiting use of "Z" Post supports to bins up to 16 rings tall	10
03/11/2016	Updated images of SuperWave Supports	20-21
03/11/2016	Added instructions for supporting floor over chain loop conveyor	29

TABLE OF CONTENTS

Introduction-----	3
Limited Warranty-----	4
Safety Section-----	5
Safety Decal Placement -----	9
“Z” Post Supports Installation Instructions-----	10
Super Supports Installation Instructions-----	14
Superwave Supports Installation Instructions-----	20
Supporting Floor Over Unload System -----	27
Supporting Floor Planks at Splices-----	33
Floor Plank Splicing-----	33
Floor Flashing Specifications -----	35
Floor and Support Layouts -----	37
Contact Information -----	80

INTRODUCTION

This product was carefully designed to give years of dependable service and was manufactured with the finest materials available. This manual includes information relating to safety and installation and should be thoroughly read prior to installation of Channel-Lok bin floor and supports. Due to the scope of projects involving material handling equipment and the wide variety of situations, this manual cannot cover all aspects. Qualified civil engineers and contractors should be relied upon for site design, layout and construction. This manual is to be used as a guideline only. The reliability, safety and good service life of this product depends to a very large extent on the care taken in installing and otherwise preparing this product for its intended use.

NOTE: This manual is for bin diameters shown on front cover.

RECEIVING AND INSPECTION

Carefully inspect materials for damage as soon as they are received. Verify that quantities of parts or packages received correspond to quantities shown on packing slip. Report any damage or shortage to delivery carrier as soon as possible. Sukup Manufacturing Co.'s responsibility for damage to materials ended with acceptance by delivery carrier. Refer to bill of lading. Save all paperwork and documentation furnished with floor components.

<p>NOTICE: Prior to installation, protect floor from weather. Do not allow moisture to become trapped between any galvanized parts.</p>
--

DISCLAIMER: Grain pressure can cause flooring to cup, especially in deeper grain (taller bins). Cupping does not constitute a floor failure, thus is not covered by Sukup Manufacturing Co. warranty.

NOTE: For instructions on installation of flush floor over aeration tunnel(s), see manual L14045, Flush Floor Aeration Installation & Owner's Manual.



Sukup Manufacturing Co.
PO Box 677 Sheffield, IA USA 50475
Phone: 641-892-4222 Fax: 641-892-4629
E-mail: Info@sukup.com Visit us at: www.sukup.com

GRAIN HANDLING & MATERIAL HANDLING LIMITED WARRANTY

SUKUP MANUFACTURING CO. (Sukup) warrants to original retail purchaser that within time limits set forth, new equipment shall be free from defects in material and workmanship. A part will not be considered defective if it substantially fulfills performance specifications. This includes cosmetic (appearance) issues that will not affect life of product. Should any part prove defective within the warranty period, the part will be replaced without charge F.O.B. Sukup Manufacturing Co., Sheffield, Iowa USA or Distribution Centers - Arcola, Illinois; Aurora, Nebraska; Defiance, Ohio; Jonesboro, Arkansas; Cameron, Missouri; Watertown, South Dakota. To obtain warranty, a copy of original invoice is required, see reverse side.

THE FOREGOING LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES OF MERCHANTABILITY, FITNESS OR PURPOSE AND OF ANY OTHER TYPE, WHETHER EXPRESS OR IMPLIED. Sukup neither assumes nor authorizes anyone to assume for it any other obligation or liability in connection with said part, and will not be liable for incidental or consequential damages. **THE REMEDIES STATED HEREIN SHALL BE THE EXCLUSIVE REMEDIES AVAILABLE UNDER THIS LIMITED WARRANTY.**

Sukup reserves the right to change specifications, add improvements or discontinue manufacture of any of its equipment without notice or obligation to purchasers of its equipment. This warranty gives you specific legal rights. You may also have other rights which vary according to state or province.

WARRANTY EXCLUSIONS - Labor, transportation, or any cost related to a service call is not provided by Sukup. This Limited Warranty does not apply to damage resulting from misuse, neglect, normal wear, accident or improper installation or maintenance. **ITEMS NOT MANUFACTURED BY SUKUP (e.g. tires, belts, motors) ARE COVERED UNDER WARRANTIES OF THEIR RESPECTIVE MANUFACTURERS AND ARE EXCLUDED FROM COVERAGE UNDER THE SUKUP WARRANTY.** Since the stirring down augers are so critical to the successful operation of the stirring machine, Sukup Manufacturing Co. will not warranty any machines unless they are equipped with Sukup down augers. **SUKUP MANUFACTURING CO. MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO DOWN AUGERS LONGER THAN 20', INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.**

Upon taking delivery of product, purchaser (dealer and/or end user) assumes responsibility for proper storage of all materials. Proper storage includes dry, temperature and humidity controlled facilities, which eliminate the potential of moisture, including condensation, from causing white rust and/or corrosion of any sort. Warranty does not extend to defects, damage or cosmetic (appearance) issues caused by improper storage or handling.

BASIC WARRANTY - All Sukup manufactured products are warranted for one year from date of purchase. Must be returned to Sukup within 30 days of failure.

EXTENDED STIRRING MACHINE WARRANTY - Sukup warrants stirring machines for two years from date of purchase.

EXTENDED STIRRING AUGER WARRANTY - Sukup warrants stirring down augers for two years from date of purchase. Must return top 18" of down auger to obtain credit.

EXTENDED FAN WARRANTY - Sukup warrants fans for two years from date of purchase.

EXTENDED HEATER CIRCUIT BOARD WARRANTY - Sukup warrants heater circuit boards for three years from date of purchase. Rebuilt circuit boards are warranted for one year from date of purchase.

EXTENDED MATERIAL HANDLING WARRANTY - Sukup warrants Material Handling, excluding structural support systems, for two years from date of purchase.

ELECTRIC MOTOR WARRANTY - The manufacturers of electric motors warranty their motors through authorized service centers for a 2 year period from motor date code. Contact motor manufacturer for nearest location. If motor warranty is refused by a service center based upon date of manufacture, use the following procedure: Have motor repair shop fill out warranty report form as if they were providing warranty service. State on report reason for refusal. Send report, motor nameplate, and proof of purchase date (invoice from Sukup and invoice for your customer) to Sukup. If electric motor warranty is not satisfactorily handled by motor service center, contact Sukup for assistance. Sukup will attempt to obtain warranty from motor manufacturer, any credit obtained will be passed on. Warranty may also be obtained by returning motor to Sukup Manufacturing Co. or Distribution Centers with prior authorization. **NOTE:** Sukup will not be responsible for unauthorized motor replacement or repair. Labor for removal of motor from fan not included.

WARRANTY CERTIFICATION - Warranty registration card should be mailed within one month of product delivery to certify warranty coverage.

UNAPPROVED PARTS OR MODIFICATION - All obligations of Sukup under this warranty are terminated if unapproved parts such as stirring augers longer than 20' are used, or if equipment is modified or altered in any way not approved by Sukup.

©3/07/16

SAFETY SECTION



Read manual before installing or using product. Failure to follow instructions and safety precautions in manual can result in death or serious injury. Keep manual in a safe location for future reference.



On safety decals, this symbol and the signal words Danger, Warning, Caution and Notice draw your attention to important instructions regarding safety.

They indicate potential hazards and levels of intensity.



RED - **DANGER** indicates an

imminently hazardous situation which, if not avoided, will result in death or serious injury.



ORANGE - **WARNING** indicates a potentially

hazardous situation which, if not avoided, could result in death or serious injury.



YELLOW - **CAUTION** indicates a potentially

hazardous situation which, if not avoided, may result in minor or moderate injury.



BLUE - **NOTICE** alerts you to practices unrelated to personal injury, such as messages related to property damage.


IMPORTANT: To prevent serious injury or death to you or your family, it is essential that safety decals are clearly visible, in good condition, and applied to the appropriate equipment.

FOLLOW MANUAL & SAFETY DECAL MESSAGES

Carefully read this manual and all safety decals on your

equipment. Safety decals must be kept in good condition. Replace missing or damaged safety decals by contacting Sukup

Manufacturing Co. via mail at PO Box 677, Sheffield, Iowa USA, 50475; by phone at 641-892-4222; or by e-mail at info@sukup.com.



It is the responsibility of the owner/operator to know what specific requirements, precautions, and work hazards exist. It is also the responsibility of the owner/operator to inform anyone operating or working in the area of this equipment of hazards and safety precautions that need to be taken to avoid personal injury or death. Always keep children away from bins and vehicles with flowing grain.

Make no unauthorized modifications to machine. Modifications may endanger function and/or safety of unit. Keep unit in good working condition. Keep shields in place. Replace worn or missing shields free of charge by contacting Sukup Manufacturing Co.

GRAIN BIN SAFETY

Owners/operators are responsible for developing site-specific confined space entry procedures. OSHA's confined space entry procedures (29CFR 1910.146) can be found at www.osha.gov.

If you must enter bin for repair or maintenance:

- Use a safety harness, safety line and respirator
- Station another person outside of bin
- Avoid the center of the bin
- Wear appropriate personal protective equipment
- Keep clear of all augers and moving parts




DANGER: Never enter bin unless all power is locked out and another person is present.



Rotating augers can kill or dismember!

NEVER enter bin when augers are running!

When bin is nearly empty, sweep auger will travel at an increasingly fast speed. Keep away from sweep and sump augers to avoid entanglement.



Failure to follow precautions above will result in death or serious injury.



DANGER: Flowing grain may trap and suffocate. If you enter a bin of flowing grain you can be completely submerged in grain in about 8 seconds.




Failure to heed this warning will result in death or serious injury.

To avoid electric shock or electrocution, all equipment must be properly wired and grounded according to electrical codes. Have unit wired by qualified electrician.



Have an electrician install a main power disconnect switch capable of being locked only in OFF position. Mark disconnect clearly as to equipment it operates. Always lock out main power disconnect switch whenever equipment is not in use.

Service Disconnect



WARNING: When servicing equipment, never enter bin unless all power is locked out and another person is present. Always LOCK OUT all power and always check with voltage meter before servicing.

Failure to do so could result in death or serious injury.

Owners/operators are responsible for developing site-specific Lockout/Tagout procedures based on equipment at their work site. See OSHA's typical minimal lockout procedures (29CFR 1910.147 App A) at www.osha.gov.

WARNING: KEEP CLEAR OF ALL MOVING PARTS


Keep people (ESPECIALLY YOUTH) away from equipment, particularly during operation.

Keep away from all moving parts. Keep all shields in place. **SHUT OFF AND LOCK OUT** all power before servicing.



Failure to follow precautions above could result in death or serious injury.

WARNING: Metal is slippery when wet. To avoid falls, never carry items if climbing on bin. Maintain secure hand and foothold if climbing on bin. Failure to do so could result in death or serious injury.



CAUTION: Metal edges are sharp. To avoid injury, wear protective clothing and handle equipment and parts with care.

Failure to do so may result in minor or moderate injury.

PERSONAL PROTECTIVE EQUIPMENT



Owners/Operators are responsible for developing site-specific personal protective equipment standards. OSHA's personal protective equipment standards (29CFR 1910.132) can be found at www.osha.gov.

Refer to OSHA 1910.132 (Personal Prot. Equip.)

EMERGENCIES – KNOW WHAT TO DO

Have emergency numbers and written directions to work site readily available in case of emergency. An area for emergency phone numbers to be recorded is provided below and at end of this manual.

Ambulance • Fire • Police: 9-1-1

Bin rescue team: _____


Emergency medical squad: _____

Address of work site: _____

Directions to work site: _____

STORED GRAIN, EQUIPMENT HAZARDS

IMPORTANT: A bin floor itself is not a hazard, but grain stored in bin and unload equipment installed in bin can create hazardous situations. Drawings below depict dangers of grain stored in bin, including obstructed flow, bridged grain, and collapse of bridged grain, all of which can engulf a person in bin. Obstructions or bridging should be removed by means other than entering bin.



Obstructed-flow, bridged grain, collapsed bridge of grain in bin

Basic Safety Rules

1. Learn how to use controls and operate equipment.
2. Do not let anyone operate equipment without thorough training of basic operating and safety procedures. Follow a proper lockout procedure.
3. Do not modify or redesign equipment without first obtaining written approval from Sukup Manufacturing Co. Unauthorized modifications to equipment may impair function and/or safety and affect machine life.
4. Periodically check all mechanical and electrical components. Keep equipment in good working condition.
5. Handle equipment and parts with care. Wear protective clothing to avoid injury from sharp metal edges.

General safety procedures must be followed when working near or on grain bins. Engulfment and burial, falling from heights, dust and mold inhalation, pesticide exposure, electrocution, and injury from augers are hazards associated with grain bins. Refer to the Sukup Bin Operation Manual, L13920, for more specific information.

IMPORTANT: Failure to follow general safety precautions may cause serious injury or death.

SAFETY QUESTIONS OR CONCERNS

Please contact Sukup Manufacturing Co. with specific safety needs regarding this equipment or its use.

NOTICE: Do not run fans unless there is a minimum of 44" of grain over entire aeration floor. Starting fans without enough weight on floor may cause supports to be pushed out of position and cause failure of floor.

NOTICE: If bin is equipped with a sidedraw, do not use at same time sumps are being used to unload grain.



FOLLOW A PROPER LOCK-OUT PROCEDURE

This suggested procedure must be performed **EVERY TIME** your equipment is to be worked on. Following these steps will assist in preventing accidents.

- Each worker must have his/her own lock and the only key to that lock.
- Make sure equipment is not operating before turning off power.
- Notify all affected employees that equipment will be locked out for service.
- Authorized employee shall refer to the facility procedure referencing the power source for the equipment.
- Shut down equipment in a normal manner.
- All energy sources that could activate the equipment must be de-activated.
- Each person who will be working on the equipment must put a lock on any energy sources that could provide any power to the equipment.
- Confirm that power has been deactivated by trying to re-start elevator.
- Turn all controls for equipment back to their “off” positions.
- **NO ONE** is to return power to equipment until all work on it has been completed and all locks have been removed.

Facility management needs to proactively train employees to ensure use of proper lockout procedures before working on the equipment. Management also needs to inspect equipment for any covers or guards not in their proper place. It is everyone’s responsibility to report any missing grates, guards, equipment failures or failures to lock out. Make certain that no cover is removed unless power is locked out.

NOTE: Refer to OSHA document 1910.147 App A for a typical minimal lockout procedure.



DANGER: Never enter bin unless all power is locked out and another person is present. Entanglement in rotating auger will cause death or serious injury.

SAFETY DECAL PLACEMENT


Two **"DANGER DO NOT ENTER this bin!"** decals, L0258A-08, are supplied with Sukup bin equipment. Both decals should be placed where people entering bin or storage building will see them.

Install one **"DANGER"** decal on bin sheet next to door, opposite of hinge side.

Install other **"DANGER"** decal next to ladder leading to roof.

One **"WARNING"** decal, L0281-15, is also supplied. It should be placed next to **"DANGER"** decal on bin sheet next to door.

If suggested locations are not in full view, place safety decals in a more suitable location. Be certain not to cover any safety decals that are already there.




It is essential that these safety decals be mounted on bin to warn and remind of potential hazards. Decals may need to be replaced if damaged or worn. Order replacement safety decals or shields free of charge by contacting Sukup Manufacturing Co. by mail at PO Box 677, Sheffield, Iowa, USA, 50475; by phone at 641-892-4222; or by e-mail at info@sukup.com. Please specify computer number. Use decal placement drawing to determine location of decals.

"Z" POST SUPPORTS INSTALLATION INSTRUCTIONS

NOTE: "Z" Post supports can be used in bins up to 16 rings tall.

Placement with one fan



NOTICE: Failure to carefully follow installation instructions will void warranty and may cause floor failure.

NOTE: For floor installation instruction using other supports, see the following pages: Super Supports, pages 14-19; SuperWave Supports, pages 20-24; concrete block, pages 25-26.

1. Determine exact bin diameter and eave height. See applicable table (pages 12-13) and floor layout (pages 38-70) to determine quantity of floor supports and spacing "A" required for each plank.
2. Determine exact center of bin. Mark chalk lines at 1/4 of support spacing "A" (See Step 1) to left and right of centerline. Continue marking parallel lines toward bin wall at 1/2 of support spacing. See Fig. 1.

NOTICE: It is essential to mark chalk lines on floor to ensure correct support spacing throughout bin. Even a few incorrectly-spaced supports may cause floor failure.

3. Take first plank (shortest) and turn upside down. Place "Z" floor support into plank. See Fig. 2. Make sure all upper tabs of support are between channels of floor plank. Place supports at spacing "A" determined in Step 1.
4. Place first plank (with supports installed) against bin wall with open channel toward you, ready to receive next plank.

IMPORTANT: Corners of first plank must touch bin wall so flashing will cover gap properly.

5. Position next row of supports. Pick up support so both notched "T" tabs are away from you. See Fig 3. Slide support against open channel so both notched "T" tabs fit over open channel. See Fig. 4.

NOTE: Do **NOT** hook tab of support under tail of floor plank. Place additional supports at support spacing "A" (shown in layout) determined in Step 1. One support should be placed at every other chalk line.

Z SUPPORTS INSTALLATION




Fig. 2




Fig. 3




Fig. 4




Fig. 5

6. Place an extra support at end of floor plank if there is more than 7" of overhang. Shorter planks used at start and finish usually require an extra support. Each side of support (if possible) should support two floor planks.
 7. Lay open channel of next floor plank on top of row of supports as shown in Fig. 5. Ensure plank is centered in bin and there is an equal distance from end of each plank to bin wall. Snap plank down into place. Check that all upper tabs of support are between channels of floor plank and are not exposed.
 8. Place next row of supports at designated support spacing "A" so they are offset from previous row by one-half the spacing distance. See Fig. 1 Use chalk lines to ensure correct spacing.
 9. Repeat Steps 5-8.
 10. After installing first few rows of flooring and supports, install a few pieces of flashing to hold floor in place. Bolt floor flashing to sidewall with bin bolts using pre-punched holes if present in sidewall sheets. Overlap flashing so sweep will "step up" as it goes around bin. See pages 35-36 for flashing installation.
- NOTE:** On smaller bins, flashing may need to be cut across center of perforated section for better fit.
11. Continue floor installation until all supports and planks are installed.
 12. Install remainder of flashing. See pages 35-36.
 13. Mount "Never Enter Bin" decal and "Safe Operation" decal near bin openings as described in safety packet A3399 (bundled with floor).

IMPORTANT: Make sure concrete is level and floor supports are placed under each floor plank. Stagger intervals as shown in Fig. 1.

“Z” POST SUPPORTS & SPACING FOR HAWK CUT FLOORS

TOTAL NUMBER OF “Z” SUPPORTS/SPACING*

BIN DIAMETER	20 GA. Z - POST REQUIREMENTS									18 GA. Z - POST REQUIREMENTS						Cont. Flow Bottom Unload **	Recirc- ulator ***
	# OF RINGS - SUKUP BINS (44" RING HEIGHT)									# OF RINGS - SUKUP BINS (44" RING HEIGHT)							
	3 & 4	5	6	7	8	9	10	11	12	13	14	15	16				
	EAVE HEIGHT (FEET)									EAVE HEIGHT (FEET)							
	16'	17' - 19'	20' - 22'	23' - 26'	27' - 30'	31' - 33'	34' - 37'	38' - 41'	42' - 44'	45' - 48'	49' - 52'	53' - 56'	57' - 59'				
12'	56-50"	56-50"	56-50"	56-50"	58-44"	58-44"	58-44"	62-43"	64-41"	66-40"	68-38"	70-36"	78-32"	86-32"	112-24"		
15'	80-54"	80-54"	86-50"	86-50"	94-44"	94-44"	94-44"	96-43"	101-41"	108-40"	110-38"	114-36"	118-32"	126-32"	159-24"		
16' 5" (5M)	98-54"	98-54"	104-50"	104-50"	118-44"	118-44"	118-44"	120-43"	122-41"	124-40"	130-38"	138-36"	150-32"	153-32"	195-24"		
18'	114-54"	114-54"	124-50"	124-50"	132-44"	132-44"	132-44"	134-43"	138-41"	138-40"	150-38"	156-36"	176-32"	184-32"	230-24"		
18' 7"	118-54"	118-54"	134-50"	134-50"	142-44"	142-44"	142-44"	145-43"	150-41"	156-40"	159-38"	168-36"	183-32"	193-32"	245-24"		
19'	122-54"	122-54"	136-50"	142-44"	142-44"	142-44"	142-44"	156-41"	162-39"	168-36"	182-34"	188-32"	208-29"	198-32"	258-24"		
19' 8" (6M)	140-54"	140-54"	148-50"	156-44"	156-44"	156-44"	156-44"	166-41"	171-39"	194-36"	200-34"	212-32"	225-29"	215-32"	276-24"		
21'	154-54"	154-54"	160-50"	180-44"	180-44"	180-44"	180-44"	187-41"	200-39"	212-36"	216-34"	236-32"	260-29"	238-32"	305-24"		
21' 8"	156-54"	156-54"	162-50"	190-44"	190-44"	190-44"	190-44"	200-41"	210-39"	218-36"	234-34"	244-32"	272-29"	252-32"	328-24"		
22' 11" (7M)	174-54"	186-50"	186-50"	204-44"	204-44"	204-44"	204-44"	226-41"	232-39"	250-36"	260-34"	280-32"	296-29"	290-32"	368-24"		
24'	184-54"	202-50"	202-50"	228-44"	228-44"	228-44"	228-44"	240-41"	246-39"	272-36"	284-34"	298-32"	330-29"	308-32"	394-24"		
24' 9"	206-54"	218-50"	218-50"	242-44"	242-44"	242-44"	242-44"	254-41"	270-39"	286-36"	304-34"	316-32"	346-29"	326-32"	422-24"		
26' 3" (8M)	244-50"	244-50"	244-50"	270-44"	296-40"	296-40"	296-40"	302-39"	320-37"	326-36"	336-34"	360-32"	396-29"	370-32"	482-24"		
27'	260-50"	260-50"	260-50"	282-44"	314-40"	314-40"	314-40"	320-39"	340-37"	344-36"	360-34"	384-32"	420-29"	383-32"	497-24"		
27' 10"	280-50"	280-50"	280-50"	310-44"	340-40"	340-40"	340-40"	354-39"	364-37"	370-36"	390-34"	418-32"	450-29"	417-32"	532-24"		
29' 6" (9M)	300-50"	300-50"	344-44"	344-44"	374-40"	374-40"	374-40"	378-39"	414-35"	456-32"	484-30"	512-28"	544-26"	466-32"	602-24"		
30'	302-50"	302-50"	346-44"	346-44"	376-40"	376-40"	376-40"	390-39"	422-35"	458-32"	496-30"	529-28"	568-26"	468-32"	612-24"		
31'	332-50"	332-50"	378-44"	378-44"	400-40"	400-40"	400-40"	418-39"	460-35"	496-32"	528-30"	560-28"	600-26"	506-32"	662-24"		
33'	380-50"	380-50"	424-44"	472-40"	472-40"	510-36"	510-36"	522-35"	550-33"	562-32"	598-30"	642-28"	684-26"	559-32"	733-24"		
34'	394-50"	394-50"	442-44"	484-40"	484-40"	532-36"	532-36"	556-35"	582-33"	602-32"	638-30"	680-28"	724-26"	612-32"	798-24"		
36'	451-50"	451-50"	490-44"	538-40"	538-40"	594-36"	594-36"	612-35"	642-33"	652-32"	706-30"	744-28"	817-26"	662-32"	878-24"		
36' 1" (11M)	465-50"	465-50"	512-44"	558-40"	558-40"	616-36"	616-36"	638-35"	666-33"	680-32"	730-30"	776-28"	833-26"	676-32"	893-24"		
37' 1"	473-50"	473-50"	524-44"	576-40"	576-40"	632-36"	632-36"	656-35"	692-33"	707-32"	761-30"	804-28"	865-26"	722-32"	938-24"		
42' Split	655-50"	714-44"	714-44"	786-40"	858-36"	970-32"	970-32"	970-32"	970-32"	970-32"	1040-29"	1146-26"	1190-25"	---	---		
42' 8" (13M) Split	680-50"	760-44"	760-44"	830-40"	900-36"	1002-32"	1002-32"	1002-32"	1002-32"	1002-32"	1096-29"	1200-26"	1252-25"	---	---		
43' 3" Split	717-50"	793-44"	793-44"	857-40"	940-36"	1039-32"	1039-32"	1039-32"	1039-32"	1039-32"	1141-29"	1257-26"	1307-25"	---	---		
48' Split	848-50"	939-44"	939-44"	1123-36"	1123-36"	1251-32"	1251-32"	1288-31"	1358-29"	1413-28"	---	---	---	---	---		
49' 3" (15M) Split	890-50"	1009-44"	1009-44"	1205-36"	1205-36"	1337-32"	1337-32"	1375-31"	1460-29"	1503-28"	---	---	---	---	---		
54' Split	1195-44"	1195-44"	1290-40"	1425-36"	1575-32"	1669-30"	1575-32"	1669-30"	---	---	---	---	---	---	---		
55' 8" Split	1253-44"	1253-44"	1370-40"	1502-36"	1668-32"	1765-30"	1668-32"	1765-30"	---	---	---	---	---	---	---		
59' 1" (18M) Split	1408-44"	1408-44"	1538-40"	1684-36"	1872-32"	1992-30"	1872-32"	1992-30"	---	---	---	---	---	---	---		
60' Split	1463-44"	1463-44"	1551-40"	1721-36"	1893-32"	2030-30"	1893-32"	2030-30"	---	---	---	---	---	---	---		
61' 10" Split	1550-44"	1550-44"	1686-40"	1863-36"	2073-32"	2195-30"	2073-32"	2195-30"	---	---	---	---	---	---	---		
72' Split	2248-40"	2467-36"	2757-32"	3119-28"	3119-28"	3119-28"	3119-28"	3255-27"	---	---	---	---	---	---	---		
75' Split	2536-40"	2778-36"	3082-32"	3484-28"	3484-28"	3484-28"	3484-28"	3598-27"	---	---	---	---	---	---	---		
78' Split	2991-36"	2991-36"	3321-32"	3747-28"	3747-28"	3747-28"	3747-28"	3880-27"	---	---	---	---	---	---	---		

*Example: 56-50" indicates a total of 56 supports at 50" spacing on each plank.

**Continuous-flow Bottom Unload: Use 20 ga. supports. Additional supports are required around center sump. Maximum grain depth is 20'.

*** If bin has a recirculating device, use 18ga floor supports with Hawk Cut flooring. Additional supports are placed around center sump. Maximum grain depth is 20'. Stirring machines are not recirculators; therefore, support spacing is based on eave height.

“Z” POST SUPPORTS & SPACING FOR .094 (STANDARD) & .050 PERFORATED CHANNEL- LOK FLOORS

TOTAL NUMBER OF “Z” SUPPORTS/SPACING*

20 GA. PERF. FLOORS - .094 (STD) OR .050 available up to 48' Diameter only							Cont. Flow Bottom Unload **
20 GA. Z - POST REQUIREMENTS							
# OF RINGS - SUKUP BINS (44" RING HEIGHT)							
	3 & 4	5	6	7	8		
BIN DIAMETER	EAVE HEIGHT (FEET)						
	16'	17' - 19'	20' - 22'	23' - 26'	27' - 30'		
12'	56-50"	56-50"	56-50"	56-50"	58-44"	112-24"	
15'	80-54"	80-54"	86-50"	86-50"	94-44"	159-24"	
16' 5" (5M)	98-54"	98-54"	104-50"	104-50"	118-44"	195-24"	
18'	114-54"	114-54"	124-50"	124-50"	132-44"	230-24"	
18' 7"	118-54"	118-54"	134-50"	134-50"	142-44"	245-24"	
19'	122-54"	122-54"	136-50"	142-44"	142-44"	258-24"	
19' 8" (6M)	140-54"	140-54"	148-50"	156-44"	156-44"	276-24"	
21'	154-54"	154-54"	160-50"	180-44"	180-44"	305-24"	
21' 8"	156-54"	156-54"	162-50"	190-44"	190-44"	328-24"	
22' 11" (7M)	174-54"	186-50"	186-50"	204-44"	204-44"	368-24"	
24'	184-54"	202-50"	202-50"	228-44"	228-44"	394-24"	
24' 9"	206-54"	218-50"	218-50"	242-44"	242-44"	422-24"	
26' 3" (8M)	244-50"	244-50"	244-50"	270-44"	296-40"	482-24"	
27'	260-50"	260-50"	260-50"	282-44"	314-40"	497-24"	
27' 10"	280-50"	280-50"	280-50"	310-44"	340-40"	532-24"	
29' 6" (9M)	300-50"	300-50"	344-44"	344-44"	374-40"	602-24"	
30'	302-50"	302-50"	346-44"	346-44"	376-40"	612-24"	
31'	332-50"	332-50"	378-44"	378-44"	400-40"	662-24"	
33'	380-50"	380-50"	424-44"	472-40"	472-40"	733-24"	
34'	394-50"	394-50"	442-44"	484-40"	484-40"	798-24"	
36'	451-50"	451-50"	490-44"	538-40"	538-40"	878-24"	
36' 1" (11M)	465-50"	465-50"	512-44"	558-40"	558-40"	893-24"	
37' 1"	473-50"	473-50"	524-44"	576-40"	576-40"	938-24"	
42' Split	655-50"	714-44"	714-44"	786-40"	858-36"	---	
42'8"(13M) Split	680-50"	760-44"	760-44"	830-40"	900-36"	---	
43' 3" Split	717-50"	793-44"	793-44"	857-40"	940-36"	---	
48' Split	848-50"	939-44"	939-44"	1123-36"	1123-36"	---	

*Example: 56-50" indicates a total of 56 supports at 50" spacing on each plank.

**Continuous-flow Bottom Unload: Use 20 ga. supports. Additional supports are required around center sump. Maximum grain depth is 20'.

NOTE: If bin has a recirculating device, use 18ga floor supports and Hawk Cut flooring. Stirring machines are not recirculators. Therefore, support spacing is based on eave height.

©11/01/15 A

SUPER SUPPORTS INSTALLATION INSTRUCTIONS

Includes Standard Super Supports and Flat Top Super Supports




Fig. 6

1. Find exact center of bin and mark it.
2. Determine where unload auger or conveyor will be located. Mark a line through center of bin along path where unload will be installed.
3. Mark lines parallel to centerline at 1/2 the support spacing given for the installation. Mark on both sides of centerline.
4. Mark lines parallel from lines at suggested spacing, continuing across floor to bin wall.
5. Start at far side of bin and place Super Supports on three or four lines on either side of center, on lines marked on floor (not centerline), with supports cupped toward centerline. When needed, place double supports down center of bin as shown.
6. Place first plank in bin. Position supports under plank so plank channel runs through cutouts in supports.
7. Place a Z Support at end of plank if there is more than 7" of overhang in bin up to 16 rings tall; if there is more than 4" of overhang in bin 17-20 rings tall; or more than 2-1/2" in bin 21 or more rings tall. Shorter planks used at start and finish usually require an extra support. Run a self-drilling screw through floor plank into stand to hold Double Super Supports in place.
8. Place next plank in bin, adjusting supports as necessary to ensure plank channels fit into cutout in supports. Add extra supports on ends if necessary. Ensure plank is centered in bin and there is an equal distance from end of each plank to bin wall. Make sure supports are spaced correctly and lie on lines marked on floor.
9. Install planks until first set of supports is almost covered. Place next support for that spacing so floor plank will rest on ends of each support without supports overlapping.
10. Repeat Steps 7 - 9.
11. After installing first few rows of flooring and supports, install a few pieces of flashing to hold floor in place. Bolt floor flashing to sidewalls using pre-punched holes if present in sidewall sheets. Overlap flashing so sweep will "step up" as it goes around bin. See pages 35-36 for flashing installation.
12. Continue installing remainder of flooring and supports.
13. Install remainder of flashing.
14. Mount "Never Enter Bin" decal and "Safe Operation" decal near bin openings as described in safety packet, A3399 (bundled with floor).




Fig. 7 – Full Super Support




Fig. 8 – Double Super Support

NOTE: Double Super Supports can be cut in half to use as singles.

See Super Supports requirements on page 17:

With recirculation devices, center half of bin is on 11” spacing; outside half is at 22”. Use 20ga Hawk Cut flooring.

NOTE: With Continuous Flow Bottom Unload and Recirculation devices, maximum grain depth is 20’. These specifications are for Hawk Cut floors. Place additional supports around center sump. Stirring machines are not recirculators; therefore, support spacing is based on eave height.

Key:

1	2
3	4

 1 = Number of Full Super Supports 2 = Super Support Spacing in inches
3 = Number of Z Supports (z) 4 = Number of Double Super Supports (d)

See Flat Top Super Supports requirements on pages 18-19:

With recirculation devices, center half of bin is on 15” spacing; outside half is at 30”. Use only with Heavy Duty Floors.

NOTE: With Continuous Flow Bottom Unload and Recirculation devices, maximum grain depth is 20’. Stirring machines are not recirculators; therefore, support spacing is based on eave height.

Key:

1	2
3	

 1 = Number of Full Super Supports 2 = Super Support Spacing in inches
3 = Number of Double Super Supports (d)




Fig. 9 – Double Super Support placement

FLAT TOP SUPER SUPPORT REQUIREMENTS FOR HEAVY DUTY, 20 GA. PERF. FLOORS

BIN DIA.	# OF RINGS - SUKUP BINS (44" RING HEIGHT)																REIRC- ULATOR						
	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18		19	20	21	22		
	EAIVE HEIGHT (FEET)																						
12'	13'	14' - 16'	17' - 19'	20' - 22'	23' - 26'	27' - 30'	31' - 33'	34' - 37'	38' - 41'	42' - 44'	45' - 48'	49' - 52'	53' - 56'	57' - 59'	60' - 63'	64' - 66'	67' - 70'	71' - 74'	75' - 78'	79' - 81'	CONT. FLOW BOTTOM UNLOAD		
16	36'	18	31'	20	28'	22	25'	20	24'	20	23'	22	21'	22	21'	22	21'	22	21'	22	20	28'	
15'	34'	26	30'	28	27'	32	25'	32	22'	34	22'	34	22'	34	22'	34	22'	34	22'	34	20	28'	
16 5' (9M)	30	32'	34	30'	34	27'	35	28	33'	28	33'	28	33'	28	33'	28	33'	28	33'	28	20	28'	
18'	32	33'	34	30'	36	27'	38	25'	46	23'	44	22'	44	21'	46	20	50	18'	60	14'	70	12'	38
18 7'	36	33'	40	29'	46	27'	46	25'	48	23'	50	22'	52	21'	56	20	60	18'	64	17'	64	12'	38
19'	34	33'	40	29'	46	27'	46	25'	48	23'	50	22'	52	21'	56	20	60	18'	64	17'	64	12'	38
19 6' (6M)	38	33'	48	29'	52	27'	52	25'	56	23'	56	22'	58	21'	62	20	62	18'	72	17'	74	12'	38
21'	46	32'	52	28'	56	26'	58	25'	64	23'	66	21'	68	20	72	18'	76	17'	80	16'	84	12'	38
21 8'	46	32'	46	28'	56	26'	58	25'	64	23'	66	21'	68	20	72	18'	76	17'	80	16'	84	12'	38
22 11' (7M)	58	32'	62	28'	66	26'	68	25'	74	23'	76	21'	78	20	84	18'	92	17'	100	16'	104	12'	38
24'	60	32'	64	28'	64	26'	70	25'	76	23'	76	21'	84	20	84	18'	92	17'	100	16'	104	12'	38
24 9'	58	32'	68	28'	68	26'	76	24'	78	23'	86	21'	88	20	90	18'	102	17'	116	15'	122	12'	38
26 5' (6M)	68	32'	76	28'	76	26'	86	24'	92	23'	94	21'	100	20	108	18'	118	17'	124	16'	132	12'	38
27'	68	32'	78	28'	82	26'	90	24'	90	23'	100	21'	104	20	108	18'	120	17'	128	16'	136	12'	38
27 10'	76	32'	88	28'	96	26'	100	24'	104	23'	114	21'	120	20	126	19'	132	17'	142	16'	150	12'	38
29 6' (9M)	82	32'	92	28'	108	26'	108	24'	110	23'	118	21'	126	20	130	19'	138	17'	144	16'	154	12'	38
30'	90	32'	106	28'	114	26'	116	24'	124	23'	132	21'	142	20	148	18'	156	17'	164	16'	174	12'	38
31'	108	30'	110	27'	124	26'	126	24'	132	23'	142	21'	154	20	160	18'	168	17'	172	16'	182	12'	38
33'	108	30'	124	27'	132	26'	144	24'	148	23'	154	21'	168	20	174	18'	182	17'	192	16'	202	12'	38
34'	122	28'	126	26'	144	24'	148	23'	154	21'	168	20	174	18'	182	17'	192	16'	202	15'	212	12'	38
36'	140	28'	156	26'	170	24'	182	22'	184	21'	198	20	202	19'	212	18'	222	17'	232	16'	242	12'	38
36 1' (11M)	142	28'	156	26'	170	24'	182	22'	184	21'	198	20	202	19'	212	18'	222	17'	232	16'	242	12'	38
37 1'	146	28'	164	26'	176	24'	184	22'	194	21'	200	20	210	19'	220	18'	230	17'	240	16'	250	12'	38
42 Split	192	28'	200	26'	220	24'	232	22'	242	21'	250	20	266	19'	276	18'	286	17'	302	16'	318	12'	38
42 8' (13M)	196	28'	212	26'	226	24'	248	22'	256	21'	270	20	276	19'	294	18'	302	17'	324	16'	348	12'	38
43 5' Split	202	28'	226	26'	248	24'	248	22'	266	21'	270	20	276	19'	294	18'	302	17'	324	16'	348	12'	38
48 Split	244	28'	262	26'	282	24'	292	22'	326	21'	342	19'	342	18'	366	16'	378	15'	426	14'	454	12'	38
49 3' (15M)	260	28'	278	26'	300	28'	308	26'	338	24'	354	19'	354	18'	374	16'	402	16'	444	14'	480	12'	38
54 Split	310	27'	330	25'	358	27'	366	24'	406	21'	426	18'	426	17'	454	15'	486	14'	514	13'	562	12'	38
55 6' Split	334	27'	360	25'	386	27'	416	21'	440	20'	466	18'	466	17'	506	15'	534	14'	574	13'	624	12'	38
59 1' (16M)	354	25'	450	23'	480	21'	494	20'	530	19'	566	18'	566	17'	614	16'	654	15'	704	14'	754	12'	38
60 Split	416	25'	482	23'	496	21'	496	20'	520	19'	562	18'	566	17'	614	16'	654	15'	704	14'	754	12'	38
61 10' Split	462	25'	486	23'	532	21'	556	20'	586	19'	636	18'	640	17'	704	16'	754	15'	804	14'	854	12'	38
72 Split	626	24'	670	22'	706	21'	738	20'	784	19'	816	18'	816	17'	874	16'	924	15'	974	14'	1024	12'	38
75 Split	654	24'	712	22'	746	21'	780	20'	812	19'	868	18'	868	17'	934	16'	984	15'	1034	14'	1084	12'	38
78 Double Split	784	23'	786	22'	874	20'	916	19'	938	18'	998	17'	1020	16'	1100	15'	1160	14'	1220	13'	1280	12'	38
90 Double Split	1080	21'	1118	20'	1182	19'	1234	18'	1318	17'	1386	16'	1464	15'	1554	14'	1656	13'	1764	12'	1878	12'	38
105' Double Split	1538	19'	1636	18'	1722	17'	1824	16'	1934	15'	2058	14'	2196	13'	2346	12'	2508	11'	2676	10'	2856	12'	38

SUPERWAVE SUPPORTS INSTALLATION INSTRUCTIONS




Image 1 – SuperWave Support

NOTE: Start floor installation on opposite side of bin from where unload auger or conveyor exits bin.

1. Find exact center of bin and mark it.
2. Determine where unload auger or conveyor will be located. Mark a line through center of bin along path where unload will be installed.
3. Mark lines parallel to centerline at 1/2 the support spacing given for the installation. See applicable table on following pages.
4. Draw lines parallel to lines at suggested spacing, continuing across floor to bin wall.
5. Start at far side of bin and place SuperWave Supports on three or four lines on each side of center, on lines marked on floor (not centerline). Position supports along lines as shown in Image 2, with tabs up. Middle two supports should be positioned up against bin wall or as close to it as possible to allow for perpendicular installation of flooring.




Image 2 – Positioning SuperWave Supports



Image 3 – Marking bin wall, installing first plank

6. Mark center of shortest floor plank. Position plank as shown in Image 3 so middle of plank lines up with mark on bin wall.
7. Holding plank upright, lower plank's lip into cutout of SuperWave Support as shown in Image 4. Ensure lip is between second and third tab of all SuperWave Supports, then lower plank into place until seated firmly. If using heavy-duty perforated flooring (See Image 5), every void between tabs in SuperWave Supports will be filled.
8. Place a Z Post Support or other support under end of plank if there is more than 7" of overhang in bin up to 16 rings tall; more than 4" of overhang in bin 17-20 rings tall; or more than 2-1/2" in bin 21 or more rings tall. Shorter planks used at start and finish usually require an extra support.
9. Place next plank in bin, adjusting supports as necessary to ensure plank channels fit into cutout in supports. Tamp plank into place. Ensure plank is centered in bin and there is an equal distance from end of each plank to bin wall. Make sure supports are on lines marked on floor.

10. Install planks until first set of supports is almost covered. Place next SuperWave Support.



Images 4 and 5 – Positioning Heavy-Duty Perforated floor plank in SuperWave Supports

11. After installing first few rows of flooring and supports, install a few pieces of flashing to hold floor in place. Bolt floor flashing to sidewalls using pre-punched holes if present in sidewall sheets. Overlap flashing pieces so sweep will “step up” as it goes around bin. See pages 35-36 for flashing installation.




Image 6 – Nesting for Hawk Cut Image 7 – Slight gap OK for HD Perf. Image 8 – Ensuring alignment

12. Repeat process, adding SuperWave Supports as installation of flooring continues toward middle of bin. **NOTICE:** Ensure that supports stay centered on floor lines. **When installing under Hawk Cut flooring, ensure that SuperWave Supports are nested end-to-end as shown in Image 6. When installing under Heavy-Duty Perforated floors there can be end-to-end gaps between SuperWave supports as shown in Image 7, but each rib of floor plank must be supported.** Small side-to-side gaps between supports will not significantly diminish support as long as supports stay on line. Edge of subsequent support can be on either side of preceding support, but it is best to be consistent. If installing long planks – 30 feet or longer – have three people putting each plank into place, one near each end and one in middle. If planks are 40 feet long, a fourth crew member will be helpful in plank installation.

NOTES: Use Double Super Supports instead of SuperWave Supports directly in front of aeration fan inlet to allow better airflow. When approaching sump and where there is not enough space to use a SuperWave Support, use Z Post Supports as shown on page 10 or use Double Super Supports.

13. Install sump as directed in appropriate unload manual. Position Super Supports (as opposed to SuperWave Supports) around sump and on side of unload between control rod and unload system. Use SuperWave Supports on other side of unload system and on rest of floor away from sump and unload system.

14. Continue installing remainder of flooring and supports.

15. Install remainder of flashing.

16. Mount “Never Enter Bin” decal and “Safe Operation” decal near bin openings as described in safety packet, A3399 (bundled with floor).

IMPORTANT: Ensure supports do not block center sump gate from opening.

SUPERWAVE™ SUPPORT REQUIREMENTS FOR HAWK CUT FLOORS

HAWK CUT AVAILABLE IN ALL SIZES 20 GA. PERF. AVAILABLE UP TO 48" DIA ONLY # OF RINGS - SUKUP BINS (44" RING HEIGHT)		HAWK CUT ONLY # OF RINGS - SUKUP BINS (44" RING HEIGHT)																																												
		3 & 4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24																								
BIN DIA.	EAVE HEIGHT (FEET)		EAVE HEIGHT (FEET)																																											
	17'-19"	20'-22"	23'-26"	27'-30"	31'-33"	34'-37"	38'-41"	42'-44"	45'-48"	49'-52"	53'-56"	57'-59"	60'-63"	64'-66"	67'-70"	71'-74"	75'-77"	78'-81"	82'-85"	86'-88"	89'-91"	92'-94"																								
15'	36	30"	36	30"	40	26"	42	22"	46	21"	46	19"	46	19"	60	15"	60	15"	60	15"	60	15"	66	14"	66	14"	72	13"	72	13"	72	13"	78	12"	78	12"	78	12"	78	12"						
18'	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z	12z					
21'	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z	34z					
24'	64	30"	64	30"	64	26"	80	22"	80	20"	80	18"	80	18"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"	108	17"				
27'	100	30"	100	30"	116	26"	136	22"	136	22"	152	19"	174	18"	174	17"	174	17"	198	15"	198	15"	198	15"	214	14"	214	14"	214	14"	232	13"	232	13"	232	13"	256	12"	256	12"	280	11"				
30'	122	30"	122	30"	136	26"	160	22"	160	22"	182	18"	202	18"	202	18"	202	18"	242	15"	242	15"	242	15"	256	14"	256	14"	282	13"	282	13"	282	13"	304	12"	304	12"	304	12"	338	11"				
33'	146	30"	146	30"	166	26"	200	22"	200	22"	258	18"	282	18"	282	18"	282	18"	286	15"	286	15"	320	14"	320	14"	346	13"	346	13"	346	13"	362	12"	362	12"	382	12"	382	12"	414	11"				
36'	166	30"	166	30"	196	26"	232	22"	232	22"	298	18"	336	17"	336	17"	336	17"	336	15"	336	15"	378	14"	378	14"	406	13"	406	13"	406	13"	440	12"	440	12"	440	12"	486	11"	486	11"				
42' Split	236	30"	268	26"	318	22"	368	19"	394	18"	478	17"	498	16"	498	16"	508	15"	508	15"	510	14"	510	14"	558	13"	558	13"	558	13"	606	12"	606	12"	606	12"	606	12"	606	12"	606	12"	666	11"		
48' Split	322	152z	350	26"	350	26"	424	22"	424	22"	522	18"	600	17"	632	16"	632	16"	650	15"	650	15"	680	14"	680	14"	738	13"	738	13"	738	13"	806	12"	806	12"	806	12"	806	12"	806	12"	885	11"		
54' Split	450	26"	532	22"	622	19"	660	18"	660	18"	782	16"	782	16"	806	15"	806	15"	850	14"	850	14"	850	14"	922	13"	922	13"	922	13"	922	13"	1018	12"	1018	12"	1018	12"	1018	12"	1018	12"	1120	11"		
60' Split	560	26"	660	22"	768	19"	818	18"	818	18"	942	16"	942	16"	1018	15"	1018	15"	1072	14"	1072	14"	1072	14"	1158	13"	1158	13"	1158	13"	1260	12"	1260	12"	1260	12"	1260	12"	1260	12"	1388	11"				
72' Split	880	26"	1046	22"	1202	18"	1290	18"	1290	18"	1440	16"	1440	16"	1534	15"	1534	15"	1688	14"	1688	14"	1688	14"	1826	13"	1826	13"	1826	13"	1998	12"	1998	12"	1998	12"	1998	12"	1998	12"	2194	11"				
78' Double Split	960	26"	1142	22"	1410	18"	1410	18"	1410	18"	1552	16"	1552	16"	1654	15"	1654	15"	1842	14"	1842	14"	1842	14"	1996	13"	1996	13"	1996	13"	2176	12"	2176	12"	2176	12"	2176	12"	2388	11"	2388	11"	2388	11"		
90' Double Split	1650	20"	1690	19"	1820	18"	1942	17"	1942	17"	2060	16"	2060	16"	2176	15"	2176	15"	2280	14"	2280	14"	2280	14"	2464	13"	2464	13"	2464	13"	2656	12"	2656	12"	2656	12"	2656	12"	2958	11"	2958	11"	2958	11"	3610	9"
105' Dbl. Split	2326	19"	2464	18"	2596	17"	2740	16"	2740	16"	2956	15"	2956	15"	3166	14"	3166	14"	3362	13"	3362	13"	3362	13"	3648	12"	3648	12"	3648	12"	4004	11"	4004	11"	4004	11"	4422	10"	4422	10"	4902	9"	4902	9"	4902	9"
450z	450z	60d	450z	60d	450z	60d	450z	60d	450z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d	426z	60d

NOTE: These specifications are for standard 7" plank Hawk Cut and Perforated floors.

Key: 1 = Number of SuperWave Supports 2 = SuperWave Support Spacing in inches
 3 = Number of Z Supports (z) 4 = Number of Double Super Supports (d)

SUPERWAVE™ SUPPORT REQUIREMENTS FOR HEAVY DUTY, 20 GA. PERF. FLOORS

BIN DIA.	# OF RINGS - SUKUP BINS (44" RING HEIGHT)																																													
	3 & 4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24																									
15'	16'	17'	19'	20'	22'	23'	26'	27'	30'	31'	33'	34'	37'	38'	41'	42'	44'	45'	53'	56'	57'	59'	60'	63'	64'	66'	67'	70'	71'	74'	75'	78'	79'	81'	82'	85'	86'	88'								
34	35	38	31	40	28	44	27	48	25	48	24	48	23	48	22	48	22	50	21	50	21	50	21	52	20	52	19	52	19	52	18	52	18	52	18	52	18	52	18	52	18	52				
4d	4d	3d	4d	4d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d	8d			
18'	34"	48	31"	52	28"	54	26"	54	25"	62	23"	62	22"	62	22"	68	21"	68	21"	72	20"	72	20"	74	19"	74	19"	74	19"	74	18"	74	18"	74	18"	74	18"	74	18"	74	18"	74	18"	74	18"	74
21'	33"	72	30"	72	28"	74	26"	76	25"	78	23"	80	22"	80	22"	86	21"	86	21"	86	20"	86	20"	88	19"	88	19"	88	19"	88	18"	88	18"	88	18"	88	18"	88	18"	88	18"	88	18"	88	18"	88
24'	33"	86	30"	90	28"	90	26"	102	24"	102	23"	112	22"	112	22"	118	21"	118	21"	120	20"	120	20"	128	19"	128	19"	128	19"	128	18"	136	17"	136	17"	136	17"	136	17"	136	17"	136	17"	136	17"	136
27'	32"	116	29"	114	27"	114	26"	132	24"	134	23"	134	22"	148	21"	148	21"	148	21"	150	20"	150	20"	150	19"	150	19"	150	19"	158	18"	158	18"	158	18"	158	18"	158	18"	158	18"	158	18"	158		
30'	32"	130	29"	148	27"	148	25"	150	24"	166	23"	166	22"	182	21"	182	21"	182	21"	188	20"	188	20"	190	19"	190	19"	190	19"	206	18"	206	18"	206	18"	206	18"	206	18"	206	18"	206	18"	206		
33'	31"	160	29"	162	27"	188	25"	188	24"	208	23"	210	22"	214	21"	230	20"	230	20"	230	19"	230	19"	230	19"	230	19"	230	19"	242	18"	242	18"	242	18"	242	18"	242	18"	242	18"	242	18"	242		
36'	31"	204	28"	202	27"	220	25"	222	24"	222	23"	244	22"	244	21"	262	20"	262	19"	262	19"	262	19"	262	19"	262	19"	262	19"	292	18"	292	18"	292	18"	292	18"	292	18"	292	18"	292	18"	292		
42' Split	30"	282	28"	308	26"	310	24"	330	23"	338	22"	338	22"	368	21"	390	20"	390	19"	390	19"	408	18"	408	18"	408	18"	408	18"	438	17"	438	17"	438	17"	438	17"	438	17"	438	17"	438	17"	438		
48' Split	29"	360	27"	388	26"	412	24"	412	23"	452	22"	452	22"	478	21"	478	20"	500	19"	500	19"	526	18"	526	18"	526	18"	526	18"	552	17"	552	17"	552	17"	552	17"	552	17"	552	17"	552	17"	552		
54' Split	29"	452	27"	480	25"	486	24"	518	23"	558	22"	558	21"	598	20"	626	19"	626	19"	626	19"	626	19"	626	19"	626	19"	626	19"	668	17"	668	17"	668	17"	668	17"	668	17"	668	17"	668	17"	668		
60' Split	28"	576	26"	576	25"	646	23"	646	22"	678	21"	678	21"	714	20"	750	19"	750	19"	750	19"	798	18"	798	18"	836	17"	836	17"	866	16"	866	16"	866	16"	866	16"	866	16"	866	16"	866	16"	866		
72' Split	20	826	25	852	24	906	23	952	22	952	21	980	20	1082	19	1082	19	1154	17	1154	17	1154	17	1154	17	1154	17	1242	16	1242	16	1242	16	1242	16	1242	16	1242	16	1242	16	1242				
75' Split	24	894	25	936	24	936	23	986	22	1026	21	1062	20	11178	19	11178	19	1200	18	1238	17	1238	17	1238	17	1238	17	1344	16	1344	16	1344	16	1344	16	1344	16	1344	16	1344	16	1344				
78' Double Split	24	1014	25	1014	24	1096	22	1096	21	1144	20	1192	20	1286	19	1340	18	1340	18	1372	17	1372	17	1372	17	1372	17	1468	16	1468	16	1468	16	1468	16	1468	16	1468	16	1468	16	1468				
90' Double Split	24	1326	24	1396	23	1466	22	1558	21	1608	20	1660	19	1660	19	1802	18	1802	18	1872	17	1872	17	1872	17	1872	17	2000	16	2000	16	2000	16	2000	16	2000	16	2000	16	2000	16	2000				
105' Double Split	40	1854	23	1912	22	2042	21	2106	20	2238	19	2370	18	2370	18	2490	17	2490	17	2606	16	2606	16	2606	16	2606	16	2786	15	2786	15	2786	15	2786	15	2786	15	2786	15	2786	15	2786				

NOTE: These specifications are for 20 ga. heavy duty Perforated floors.

Key: 1 = Number of SuperWave Supports 2 = SuperWave Support Spacing in inches

2 = SuperWave Support Spacing in inches

4 = Number of Double Super Supports (d)

1
2
4

SUPERWAVE™ SUPPORT REQUIREMENTS FOR HEAVY DUTY, 18 GA. PERF. FLOORS

BIN DIA.	# OF RINGS - SUKUP BINS (44" RING HEIGHT)																				
	3 & 4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
15'	EAVE HEIGHT (FEET)																				
16'	17' - 19'	20' - 22'	23' - 26'	27' - 30'	31' - 33'	34' - 37'	38' - 41'	42' - 44'	45' - 48'	49' - 52'	53' - 56'	57' - 59'	60' - 63'	64' - 66'	67' - 70'	71' - 74'	75' - 78'	79' - 81'	82' - 85'	86' - 88'	
18'	32	39 ³ 34	35 ³ 38	33 ³ 38	30 ³ 38	29 ⁴ 44	27 ⁴ 44	26 ⁴ 48	25 ⁴ 48	24 ⁴ 48	23 ⁴ 48	23 ⁴ 48	23 ⁴ 48	22 ⁴ 50	21 ⁴ 50	21 ⁴ 52	20 ⁴ 52	20 ⁴ 52	20 ⁴ 52	19 ⁴ 52	
21'	42	38 ⁴ 42	35 ⁴ 48	32 ⁴ 50	30 ⁴ 52	28 ⁴ 54	27 ⁴ 54	26 ⁴ 58	24 ⁴ 62	23 ⁴ 62	22 ⁴ 62	21 ⁴ 68	21 ⁴ 68	21 ⁴ 68	21 ⁴ 72	20 ⁴ 72	20 ⁴ 72	20 ⁴ 72	20 ⁴ 74	19 ⁴ 74	
24'	62	38 ⁷ 72	34 ⁷ 72	32 ⁷ 72	30 ⁷ 72	28 ⁷ 72	27 ⁷ 76	25 ⁷ 78	24 ⁷ 78	23 ⁷ 80	22 ⁷ 80	21 ⁷ 86	21 ⁷ 86	21 ⁷ 86	20 ⁷ 86	20 ⁷ 86	20 ⁷ 86	20 ⁷ 86	19 ⁷ 86	19 ⁷ 86	
27'	80	37 ⁸ 80	34 ⁸ 82	32 ⁸ 86	30 ⁸ 90	28 ⁸ 90	26 ⁸ 102	25 ⁸ 102	24 ⁸ 102	23 ⁸ 102	22 ⁸ 112	21 ⁸ 118	21 ⁸ 118	21 ⁸ 118	20 ⁸ 128	20 ⁸ 128	19 ⁸ 128	19 ⁸ 136	18 ⁸ 136	18 ⁸ 136	
30'	78	37 ⁸ 96	34 ⁸ 96	31 ⁸ 116	29 ⁸ 118	28 ⁸ 114	26 ⁸ 120	25 ⁸ 132	24 ⁸ 134	23 ⁸ 134	22 ⁸ 134	21 ⁸ 148	21 ⁸ 148	21 ⁸ 150	20 ⁸ 150	20 ⁸ 150	19 ⁸ 150	19 ⁸ 158	18 ⁸ 158	18 ⁸ 158	
33'	110	36 ⁹ 110	33 ⁹ 128	31 ⁹ 130	29 ⁹ 148	27 ⁹ 148	26 ⁹ 148	25 ⁹ 150	24 ⁹ 166	23 ⁹ 166	22 ⁹ 182	21 ⁹ 182	21 ⁹ 182	21 ⁹ 188	20 ⁹ 190	19 ⁹ 190	19 ⁹ 206	18 ⁹ 206	18 ⁹ 206	18 ⁹ 206	
36'	118	36 ⁹ 136	33 ⁹ 148	31 ⁹ 160	29 ⁹ 162	27 ⁹ 188	26 ⁹ 188	25 ⁹ 188	24 ⁹ 208	23 ⁹ 210	22 ⁹ 214	21 ⁹ 214	21 ⁹ 214	21 ⁹ 230	20 ⁹ 230	19 ⁹ 242	18 ⁹ 242	18 ⁹ 242	18 ⁹ 242	18 ⁹ 242	
42' Split	128	35 ¹⁰ 178	33 ¹⁰ 178	30 ¹⁰ 180	29 ¹⁰ 202	27 ¹⁰ 204	26 ¹⁰ 220	25 ¹⁰ 222	24 ¹⁰ 222	23 ¹⁰ 244	22 ¹⁰ 244	21 ¹⁰ 244	21 ¹⁰ 262	20 ¹⁰ 262	20 ¹⁰ 262	20 ¹⁰ 292	18 ¹⁰ 292	18 ¹⁰ 310	17 ¹⁰ 310	17 ¹⁰ 310	
48' Split	168	34 ¹¹ 254	32 ¹¹ 254	30 ¹¹ 282	28 ¹¹ 282	27 ¹¹ 308	25 ¹¹ 310	24 ¹¹ 330	23 ¹¹ 338	22 ¹¹ 338	22 ¹¹ 368	21 ¹¹ 390	20 ¹¹ 390	20 ¹¹ 390	19 ¹¹ 390	19 ¹¹ 408	18 ¹¹ 408	18 ¹¹ 438	17 ¹¹ 438	17 ¹¹ 438	
54' Split	284	34 ¹² 320	31 ¹² 350	29 ¹² 350	28 ¹² 388	26 ¹² 388	25 ¹² 412	24 ¹² 412	23 ¹² 452	22 ¹² 478	21 ¹² 478	21 ¹² 478	20 ¹² 478	20 ¹² 478	19 ¹² 500	18 ¹² 526	18 ¹² 526	17 ¹² 552	17 ¹² 552	17 ¹² 552	
60' Split	390	33 ¹³ 390	31 ¹³ 424	29 ¹³ 452	27 ¹³ 452	26 ¹³ 480	25 ¹³ 486	24 ¹³ 518	23 ¹³ 558	22 ¹³ 558	21 ¹³ 558	21 ¹³ 598	20 ¹³ 626	19 ¹³ 626	18 ¹³ 626	18 ¹³ 668	17 ¹³ 668	17 ¹³ 668	17 ¹³ 668	17 ¹³ 668	
72' Split	480	32 ¹⁴ 496	30 ¹⁴ 542	28 ¹⁴ 544	27 ¹⁴ 576	25 ¹⁴ 610	24 ¹⁴ 646	23 ¹⁴ 646	22 ¹⁴ 678	21 ¹⁴ 714	20 ¹⁴ 714	20 ¹⁴ 758	19 ¹⁴ 758	18 ¹⁴ 758	18 ¹⁴ 836	17 ¹⁴ 836	17 ¹⁴ 866	16 ¹⁴ 954	15 ¹⁴ 954	15 ¹⁴ 954	
75' Split	712	31 ¹⁵ 736	29 ¹⁵ 770	27 ¹⁵ 826	26 ¹⁵ 826	25 ¹⁵ 852	24 ¹⁵ 906	23 ¹⁵ 952	22 ¹⁵ 952	21 ¹⁵ 952	20 ¹⁵ 980	19 ¹⁵ 1082	18 ¹⁵ 1124	18 ¹⁵ 1124	18 ¹⁵ 1154	17 ¹⁵ 1242	16 ¹⁵ 1304	15 ¹⁵ 1304	15 ¹⁵ 1424	14 ¹⁵ 1424	
78' Double Split	738	31 ¹⁶ 750	29 ¹⁶ 832	27 ¹⁶ 846	26 ¹⁶ 894	25 ¹⁶ 936	24 ¹⁶ 936	23 ¹⁶ 982	22 ¹⁶ 1026	21 ¹⁶ 1062	20 ¹⁶ 1178	19 ¹⁶ 1178	19 ¹⁶ 1200	18 ¹⁶ 1200	18 ¹⁶ 1238	17 ¹⁶ 1344	16 ¹⁶ 1422	15 ¹⁶ 1422	15 ¹⁶ 1514	14 ¹⁶ 1514	
90' Double Split	886	30 ¹⁷ 932	28 ¹⁷ 932	27 ¹⁷ 960	26 ¹⁷ 1014	25 ¹⁷ 1014	24 ¹⁷ 1054	23 ¹⁷ 1096	22 ¹⁷ 1144	21 ¹⁷ 1192	20 ¹⁷ 1286	19 ¹⁷ 1286	19 ¹⁷ 1340	18 ¹⁷ 1372	17 ¹⁷ 1468	16 ¹⁷ 1556	15 ¹⁷ 1556	15 ¹⁷ 1652	14 ¹⁷ 1652	14 ¹⁷ 1652	
105' Double Split	1082	29 ¹⁸ 1176	28 ¹⁸ 1294	26 ¹⁸ 1280	25 ¹⁸ 1326	24 ¹⁸ 1396	23 ¹⁸ 1466	22 ¹⁸ 1558	21 ¹⁸ 1608	20 ¹⁸ 1608	19 ¹⁸ 1660	19 ¹⁸ 1660	19 ¹⁸ 1802	18 ¹⁸ 1872	17 ¹⁸ 2000	16 ¹⁸ 2000	16 ¹⁸ 2082	15 ¹⁸ 2176	14 ¹⁸ 2176	14 ¹⁸ 2340	
Split	1542	28 ¹⁹ 1600	27 ¹⁹ 1732	25 ¹⁹ 1794	24 ¹⁹ 1854	23 ¹⁹ 1912	22 ¹⁹ 1912	22 ¹⁹ 2042	21 ¹⁹ 2106	20 ¹⁹ 2106	19 ¹⁹ 2238	19 ¹⁹ 2238	18 ¹⁹ 2370	17 ¹⁹ 2606	16 ¹⁹ 2606	16 ¹⁹ 2786	15 ¹⁹ 2964	14 ¹⁹ 2964	14 ¹⁹ 3132	13 ¹⁹ 3132	

NOTE: These specifications are for 18 ga. heavy duty Perforated floors.

Key:

1
2
4

1 = Number of SuperWave Supports

2 = SuperWave Support Spacing in inches

4 = Number of Double Super Supports (d)

FLOOR INSTALLATION USING CONCRETE BLOCKS FOR STIR DRYING BINS AND STORAGE BINS

1. Refer to Concrete Block Spacing and Quantity Recommendation Chart before beginning assembly.

IMPORTANT: When using a recirculating device or continuous-flow bottom unload system, floor supported by concrete blocks requires intermediate support braces below floor. Check with recirculator or continuous flow unload system manufacturer and purchase intermediate braces from them. Otherwise, “Z” Post floor supports are recommended when installing recirculator or continuous flow bottom unload system. Maximum grain depth with recirculator or continuous flow bottom unload system is 20'.

Stirring machines are not recirculators; therefore, support spacing is based on eave height.

2. Chalk-mark centerline of bin in same direction unloading tube will run.

3. Measure over one-half of the “B” dimension on either side of centerline and chalk-mark another line. Continue to measure over the “B” dimension from these lines until reaching bin wall. When complete, there should be a set of parallel lines “B” dimension apart.

4. Place concrete blocks around perimeter of bin, staying 2-3 inches from bin wall. Place rows of concrete blocks so they are centered on chalk lines and so air will flow horizontally through holes in blocks. See Fig. 10.

IMPORTANT: If installing a split-plank floor, ensure splices are supported by concrete blocks. It may be necessary to move those blocks 1” off of center of chalk lines to ensure proper support of plank splices. See plank splicing instructions on Page 34.

NOTICE: Be sure center sump is supported adequately by concrete blocks. It may be necessary to stagger blocks around center sump to provide proper support. Be sure no blocks will interfere with travel of center sump slide gate.



5. Start laying floor by using shortest floor plank first. Open-channel edge of floor must face center of bin. Second piece of floor may be snapped into place by pushing down on inside edge of floor. Refer to proper bin diameter Channel-Lok floor layout page to find specified floor plank lengths and order in which they are assembled.

6. Continue this procedure with remainder of floor. On longer pieces it may be necessary to snap floor pieces together starting at one end and gradually moving toward other end.


7. When floor has been installed, refer to Floor Flashing Detail pages, 35-36, for instructions on installing floor flashing.

WARRANTY VALID ONLY WHEN CONCRETE IS LEVEL AND FLOORING IS INSTALLED ACCORDING TO CHANNEL-LOK SPECIFICATIONS AND INSTRUCTIONS.

CONCRETE BLOCK SPACING AND QUANTITY RECOMMENDATIONS



Section X-X
Typical block spacing 8" x 8" x 16" blocks.



Section X-X
Typical block spacing for recirculating and continuous flow bottom unload systems.

NOTE: Due to high temperatures and airflows required for continuous flow drying, concrete blocks are not recommended.

Fig. 10 – Concrete block floor supports

IMPORTANT: See previous page for plank installation instructions.
Maximum peak grain depth on concrete (with no steel supports) is:

Hawk Cut floor - 40'
20 gauge Round Hole Perforated Floor - 20'

CHART BELOW (QUANTITIES) IS FOR TWO HIGH BLOCK

BIN DIA	EAVE HEIGHT						RECIRCULATOR & CONT. FLOW (1) BOTTOM UNLOAD	
	Up to 20		21'-30'		31'-34'			
	Qty.	"B"	Qty.	"B"	Qty.	"B"	Qty.	"B"
15'	120	26"	---	---	---	---	---	---
18'	180	24"	235	17"	23	17"	276	18"
21'	270	22"	330	17"	330	17"	370	18"
24'	340	22"	400	17"	500	13"	500	18"
27'	410	22"	560	16"	640	13"	626	18"
30'	500	22"	675	16"	785	13"	755	18"
33'	610	22"	790	16"	1010	13"	936	18"
36'	725	22"	936	16"	1200	13"	1110	18"
42'	1080	20"	1300	16"	1570	13"	1510	18"
48'	1330	20"	1640	16"	NR	NR	NR	NR

(1) Maximum eave height 20'. Recirculator requires use of intermediate support brace centered under each plank. See previous page.

SUPPORTING FLOOR OVER UNLOAD SYSTEM

In addition to floor supports specified in flooring installation instructions, supports such as Sukup Double Super Supports must be placed along unload auger or conveyor to provide adequate floor support.

IMPORTANT: Refer to specific floor support instructions on this and following pages for unload system used.

DISCLAIMER: It shall not be the responsibility of Sukup Manufacturing Co. to determine suitable support system for flooring over unload system. Customer (or customer's retained engineer or construction supervisor) is responsible. Consideration should include, but not be limited to, live loads, dead loads and seismic zone.

Sukup Manufacturing Co. will not be responsible for any damage to a product, including, but not limited to, any damage that results from inadequate or improper support methods and materials.

Supporting Floor Over Unload Tube

If applicable table elsewhere in this manual (for type of supports used under floor) says supports should be placed closer than Dimension A in table below, then bridging is needed to support floor planks over void left for sump gate when it is open, as shown in Fig. 11.




Fig. 11

UNLOAD TUBE DIA.	DIMENSION A	EAVE HEIGHT	
		48' OR LESS	54'-78'
6"	16"	68'	64'
8"-10"	23"	48'	44'

If bridging is recommended, it should be at center of each floor plank over unload tube. Bridging supports should at minimum be made of 1-1/2 x 1-1/2" high-strength steel tube with a thickness of 3/16", or material of similar strength. Bridging tubes must be kept from sliding off of supports using tabs, screws or other means. **IMPORTANT:** Floor supports used for bridging do not count as part of floor support system.

If using Double Super Supports, place on each side of sump and unload tube as shown in Fig. 11, making sure to anchor Double Super Support bases to concrete using concrete screws or wedge anchors.

Two bridging tubes must be used under each plank if eave height of bin is greater than height listed in table above. Also, two Double Super Supports must be placed on each side of sump and unload tube if using two floor support tubes under each plank. Values in table above are based on 15-7/8" floor supports and assume unload is not in a trench.

Supporting Floor Over U-Trough

In addition to floor supports specified in flooring installation instructions, supports such as Sukup Double Super Supports must be placed between U-Trough and clutch rod as shown in Fig. 12 to provide adequate floor support above trough.




Fig. 12

If applicable table elsewhere in this manual (for type of supports used under floor) says supports should be placed closer than width of trough, bridging is needed to support floor planks over trough.

If bridging is recommended, it should be at center of each floor plank over trough. Bridging supports should at minimum be made of 1-1/2 x 1-1/2" high-strength steel tube with a thickness of 3/16", or material of similar strength. Bridging tubes must be kept from sliding off of supports using tabs, screws or other means. **IMPORTANT:** Floor supports used for bridging do not count as part of floor support system.

If using Double Super Supports, place on each side of sump and unload trough as shown in Fig. 12, making sure to anchor Double Super Support bases to concrete using concrete screws or wedge anchors.

EAVE HEIGHT	
48' OR LESS	54'-78'
68'	64'
48'	44'

Two bridging tubes must be used under each plank if eave height of bin is greater than height listed in table above. Also, two Double Super Supports must be placed on each side of sump and trough if using two floor support tubes under each plank. Values in table above are based on 15-7/8" floor supports and assume trough is not in a trench.

Supporting Floor Over Chain Loop Conveyor

In addition to floor supports specified in flooring installation instructions, supports such as Sukup Double Super Supports should be placed as close as possible to conveyor tube as shown in Fig. 13 to provide adequate floor support. However, be sure to leave voids for opening of sump gates.

Additionally, if table elsewhere in this manual says floor supports should be placed closer than allowed by diameter of conveyor tube or width of center or intermediate sump gates, then bridging is needed to support floor planks in those areas. See Fig. 13 and table above it.

Following is guidance to consider. If bridging is recommended, it should be at center of each floor plank. Bridging supports should at minimum be made of 1-1/2 x 1-1/2" high-strength steel tube with a thickness of 3/16", or material of similar strength. Bridging tubes must be kept from sliding off of supports using tabs, screws or other means. **IMPORTANT:** Floor supports used for bridging do not count as part of floor support system. See tables elsewhere in this manual for floor support requirements.

If using Double Super Supports, place on each side of unsupported area as shown in Fig. 13, making sure to anchor Double Super Support bases to concrete using concrete screws or wedge anchors.

Single-tube bridging is adequate to span distances shown by eave heights in table under Fig. 13; two (2) tubes are required for spans exceeding those distances. Also, two Double Super Supports must be placed on each side of sump and conveyor if using two floor support tubes under each plank. Values are based on 15-7/8" floor supports and assume conveyor is not in a trench.

LOOP SYSTEM SIZE	DIM. A	DIM. B	DIM. C
8"	16"	14"	8"
10"	16"	14"	10"
12"	20"	16"	12"

NOTE: Dimensions are approximate




Fig. 13

OPEN SPAN DISTANCE	BIN DIA./EAVE HEIGHT		
	48' or less	54' to 78'	90' to 105'
16" or more	68'	64'	61'
20" or more	56'	52'	49'

After supports are in place, install floor as described elsewhere in this manual.


Supporting Floor Over Conveyor

Following is guidance to consider, applicable to bins up to 105 feet in diameter and 24 rings tall. Each floor plank over conveyor should be supported at center of plank by bridging. Bridging supports should at minimum be made of 1-1/2 x 1-1/2" high-strength steel tube with a thickness of 3/16", or material of similar strength. Bridging tubes must be kept from sliding off of supports, such as Sukup Double Super Supports, using tabs, screws or other means. **IMPORTANT:** Floor supports used for bridging do not count as part of floor support system.

If using Double Super Supports, place on each side of sump and conveyor as shown in Figs. 14-16, making sure to anchor Double Super Support bases to concrete using concrete screws or wedge anchors. Table below shows distance (Dimension A) between inside edges of Double Super Supports. Values in table are based on 15-7/8" floor supports and assume conveyor is not in a trench.

CONVEYOR WIDTH	MAX. "A" DIM.	EAVE HEIGHT		
		48' & SMALLER BINS	54-78' BINS	90-105' BINS
9"	14"	81"	77"	73"
12"	17"	68'	64'	61'
16"	21"	56'	52'	49'
21"	26"	48'	44'	41'

Floor supports must be placed as close to sides of sump as possible, as shown in Fig. 14.



SWDC0091 SHEET 1
06/24/2016 TAW

Fig. 14 – Positioning Double Super Supports

Refer to Fig. 15 for supporting flooring over conveyor in bins with eave heights listed in table on previous page. Refer to Fig. 16 for bins with eave heights greater than listed in table on previous page.

FLOOR PLANKS MUST BE SUPPORTED NEAR CONVEYOR
USING Z POSTS, SUPERWAVE SUPPORTS, AND/OR
FULL SUPER SUPPORT AS SHOWN BELOW.




Fig. 15 – Planks over conveyor, shown from above and side

As shown in Fig. 16, two tubes must be used under each plank if eave height is greater than height listed in table on page 30. Also, two Double Super Supports must be placed on each side of sump and conveyor if using two floor support tubes under each plank. See Fig. 14.

NOTE: If recommended number of Double Super Supports do not fit under floor planks, contact structural engineer or Sukup Manufacturing Co. for other options.




Fig. 16 – Planks over conveyor supported by two tubes and two Double Super Supports, shown from above and from side

SUPPORTING FLOOR PLANKS AT SPLICES

Ends of floor planks must not extend more than 7" beyond floor supports in bins up to 16 rings tall; more than 4" in bins 17 to 20 rings tall; or more than 2-1/2" in bins 21 or more rings tall. If either floor plank at splice has a longer unsupported overhang, additional supports will be needed. See Fig. 17.

NOTE: If bin has 21 or more rings, a support must be placed 2", plus or minus 1/2", from edge of each plank at splice, no matter which type of supports are used in bin.

NOTE: No floor support should be closer than 1-1/2" from end of a plank at splice.




Fig. 17 – Supporting floor planks at splices

FLOOR PLANK SPLICING




Fig. 18 – Splicing floor planks

If bin floor plank is made up of two pieces, they must be joined together with a splice. Using self-drilling screws, join two pieces of floor plank by fastening perforated splice as shown in Fig. 18.

FLOOR FLASHING SPECIFICATIONS

Specifications by floor height

HEIGHT	STANDARD				HIGH BACK	
	A	B	C	D	C	D
5-1/4"	5-3/8"	4"	6"	7"	7-1/4"	8-1/4"
13-1/4"	13-3/8"	12"	14"	15"	15-1/4"	16-1/4"
15-7/8"	16"	14-5/8"	16-5/8"	17-5/8"	17-7/8"	18-7/8"
*17"	17-1/8"	15-3/4"	17-3/4"	18-3/4"	19"	20"
18-1/2"	18-5/8"	17-1/4"	19-1/4"	20-1/4"	20-1/2"	21-1/2"

***17" not available in Super Supports.**

A = Measurement from concrete to top of floor.

B = Measurement from concrete to bottom of floor.

C = Approximate distance from bottom of slot to concrete.

D = Approximate distance from top of slot to concrete.




Fig. 19 – Floor flashing specifications

Shipping List

Flashing and Hardware for Bin Floor


BIN FLOOR SIZE	PIECES OF FLASHING*	FLASHING SCREWS	5/16 NUTS	3/8" WASHERS
15'	60	124	62	62
18'	72	156	78	78
21'	84	176	88	88
24'	96	200	100	100
27'	108	224	112	112
30'	120	252	126	126
33'	132	272	136	136
36'	144	300	150	150
42' split	168	348	174	174
48' split	192	396	198	198
54' split	228	448	224	224
60' split	240	484	242	242
72' split	288	580	290	290
75' split	300	604	302	302
78' split	312	628	314	314
90' split	360	724	362	362
105' split	420	846	423	423

* If flashing is ordered pre-punched for Airways, pieces that are not pre-punched go under bin door.

FLASHING REQUIRED = 4 X BIN DIAMETER

FLOOR FLASHING DETAIL

If sweep auger will be used in bin, flashing must be overlapped as shown in Fig. 20 so that sweep wheel will "climb up" flashing sections as sweep travels clockwise around bin. This will prevent wheel from catching on edges of flashing. Reverse overlap if sweep will run counterclockwise.



5/16 BIN BOLT
J0537




Fig. 20 – Flashing installation

Install #10 x 3/4" flashing screw at corner of each piece of flashing so screw goes through two pieces of flashing. See Fig. 20. Install a screw in flashing where two planks meet more than 2" from corner of flashing. See Fig. 21 or Fig. 22 to properly bolt flashing to side of bin depending on location of pre-punched plenum holes.

IMPORTANT: Use same bolt size as used in vertical seams of sidewall sheets.

Fig. 21 – Bolting on hill





Fig. 22 – Bolting in valley



*Bin bolts and neoprene washers not included with flashing.
 **Refer to previous page to confirm flashing style and hole location.

Notes on Floor Plank Location Tables and Support Installation

Included with each of the following floor layout pages are “Locating Floor Planks” tables. Please read them carefully to help in sorting planks according to bundle and length before beginning floor assembly.

See applicable table for spacing and total number of supports based on bin eave height. Tables for Z-Post Supports are on pages 12-13; for Super Supports are on pages 17-19; and for SuperWave Supports are on pages 22-24.

Place supports under each plank and install according to applicable instructions. Ends of floor planks must not extend more than 7” beyond floor supports in bins up to 16 rings tall; more than 4” in bins 17-20 rings tall; or more than 2-1/2” in bins 21 or more rings tall. See Page 33. Ensure that support closest to end of each plank also supports both adjacent planks.

Floors in 36’, 42’ and 48’ dia. bins can be ordered split or non-split. Floors in bins larger than 48’ in diameter are all split-plank floors.


The following note applies to tables for split floors in bins 36’ in diameter and larger:

- Lengths of two split pieces are shown for each plank number.
- Seams in split floor must alternate as shown in plank layout drawing for bin.
- On split planks, increase number of supports listed for each plank so a support will be on each side of splice.
- See page 34 for splicing instructions.

There is only one plank “0” and two of all others (one on each side of centerline) for floors in bins 15’, 21’, 27’, 33’, 36’, 48’, 60’, 72’, 75’, 78’, 90’ or 105’ in diameter:

FLOOR AND SUPPORT LAYOUTS

15' DIAMETER BIN – FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 15' BIN

A 15' floor is shipped in one bundle. It will contain two stacks of flooring.


1. Label stacks as shown below by measuring top plank of each stack.
2. To find starter plank, see 15' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 12, measuring 2' 4") is starter plank.
3. Install by following applicable floor support instructions.
4. Lay out remaining planks of Stack No. 1. Work in descending order from plank No. 12 to plank No. 0, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

15' FLOOR

Stack No. 1		Stack No. 2	
Plank Number	Plank Length	Plank Number	Plank Length
<i>Top of stack</i>			
12	2' 4"	12	2' 4"
11	6' 1"	11	6' 1"
10	8' 2"		
		10	8' 2"
9	9' 9"	9	9' 9"
8	10' 11"		
		8	10' 11"
7	11' 11"	7	11' 11"
6	12' 8"		
		6	12' 8"
5	13' 4"	5	13' 4"
4	13' 9"		
		4	13' 9"
3	14'	3	14"
2	14' 3"		
		2	14' 3"
1	14' 4"	1	14' 4"
0	14' 4"		
<i>Bottom of stack</i>			

18' DIAMETER BIN – FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 18' BIN

An 18' floor is shipped in one bundle. It will contain two identical stacks of flooring.

1. To find starter plank, see 18' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 15, measuring 2' 11") is starter plank.
2. Install using applicable floor support instructions.
3. Work in descending order from plank No. 15 to plank No. 1 using applicable floor support instructions, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

18' FLOOR

Stacks No. 1 & No. 2


Plank Plank
Number Length

Top of Stack

15	2' 11"
14	6' 10"
13	9' 2"
12	10' 10"
11	12' 3"
10	13' 4"
9	14' 3"
8	15' 1"
7	15' 9"
6	16' 3"
5	16' 8"
4	16' 11"
3	17' 2"
2	17' 3"
1	17' 4"

Bottom of Stack

21' DIAMETER BIN - FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 21' BIN

A 21' floor is shipped in one bundle. It will contain two stacks of flooring.


1. Label stacks as shown below by measuring top plank of each stack.
2. To find starter plank, see 21' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 17, measuring 3' 5") is starter plank.
3. Install by following applicable floor support instructions.
4. Lay out remaining planks of Stack No. 1. Work in descending order from plank No. 17 to plank No. 0, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

21' FLOOR

Stack No. 1		Stack No. 2	
Plank Number	Plank Length	Plank Length	Plank Number
<i>Top of Stack</i>			
13	13' 5"	15	10'
12	14' 8"	14	11' 11"
17	3' 5"	17	3' 5"
14	11' 11"	16	7' 7"
11	15' 9"	13	13' 5"
10	16' 8"	12	14' 8"
9	17' 6"	11	15' 9"
8	18' 2"	10	16' 8"
7	18' 9"	9	17' 6"
6	19' 3"	8	18' 2"
5	19' 7"	7	18' 9"
4	19' 10"	6	19' 3"
3	20' 1"	5	19' 7"
2	20' 3"	4	19' 10"
1	20' 3"	3	20' 1"
16	7' 7"	2	20' 3"
15	10'	1	20' 3"
0	20' 3"		
<i>Bottom of Stack</i>			

24' DIAMETER BIN - FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 24' BIN

A 24' floor is shipped in one bundle. It will contain two identical stacks of flooring.

1. To find starter plank, see 24' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 20, measuring 4') is starter plank.
2. Install using applicable floor support instructions.
3. Work in descending order from plank No. 20 to plank No. 1 using applicable floor support instructions, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

24' FLOOR

Stacks No. 1 & No. 2
Plank Plank
Number Length

Top of Stack

16	14' 6"
15	15' 11"

20	4'
17	12' 11"
14	17' 2"

13	18' 2"
12	19' 1"

19	8' 3"
18	10' 11"
11	19' 11"

10	20' 7"
9	21' 3"

8	21' 9"
7	22' 2"


6	22' 6"
5	22' 9"

4	23'
3	23' 2"

2	23' 3"
1	23' 3"

Bottom of Stack

27' DIAMETER BIN - FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 27' BIN

A 27' floor is shipped in one bundle. It will contain two stacks of flooring.

1. Label stacks as shown below by measuring top plank of each stack.
2. To find starter plank, see 27' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 22, measuring 4' 7") is starter plank.
3. Install by following applicable floor support instructions.
4. Lay out remaining planks of Stack No. 1. Work in descending order from plank No. 22 to plank No. 0, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

27' FLOOR


Stack No. 1		Stack No. 2	
Plank Number	Plank Length	Plank Length	Plank Number

Top of Stack

22	4' 7"	22	4' 7"
21	8' 11"	21	8' 11"
20	11' 8"		
19	13' 10"	20	11' 8"
18	15' 7"	19	13' 10"
17	17' 1"	18	15' 7"
16	18' 5"	17	17' 1"
15	19' 7"	16	18' 5"
14	20' 7"	15	19' 7"
13	21' 6"	14	20' 7"
12	22' 4"	13	21' 6"
11	23'	12	22' 4"
10	23' 8"	11	23'
9	24' 3"	10	23' 8"
8	24' 8"	9	24' 3"
7	25' 1"	8	24' 8"
6	25' 5"	7	25' 1"
5	25' 8"	6	25' 5"
4	25' 11"	5	25' 8"
3	26' 1"	4	25' 11"
2	26' 2"	3	26' 1"
1	26' 3"	2	26' 2"
0	26' 3"	1	26' 3"

Bottom of Stack

30' DIAMETER BIN – FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 30' BIN

A 30' floor is shipped in one bundle. It will contain two identical stacks of flooring.

1. To find starter plank, see 30' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 25, measuring 5' 2") is starter plank.
2. Install using applicable floor support instructions.
3. Work in descending order from plank No. 25 to plank No. 1 using applicable floor support instructions, then open Stack No. 2 and work from largest to smallest.

See page 37 for important notes.

30' FLOOR


Stacks No. 1 & No. 2
Plank Plank
Number Length

Top of Stack

25	5' 2"
24	9' 7"
23	12' 6"
22	14' 9"
21	16' 7"
20	18' 3"
19	19' 7"
18	20' 10"
17	22'
16	23'
15	23' 11"
14	24' 9"
13	25' 5"
12	26' 1"
11	26' 8"
10	27' 3"
9	27' 8"
8	28'
7	28' 4"
6	28' 7"
5	28' 10"
4	29'
3	29' 1"
2	29' 2"
1	29' 3"

Bottom of Stack

33' DIAMETER BIN – FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 33' BIN

A 33' floor is shipped in two large bundles. Each will contain two smaller bundles of flooring.


1. Lay out these four bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, see 33' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 27, measuring 5' 9") is starter plank. There is a Plank No. 27 in bundle No. 1 and in bundle No. 2. They are shortest planks in bundles.
4. Lay out remaining planks. Work in descending order from plank No. 27 to plank No. 0, breaking open additional bundles as needed.

See page 37 for important notes.

33' FLOOR

Bundle No. 1				Bundle No. 2			
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
Top of Bundle							
23	17' 7"			13	28' 6"	14	27' 10"
22	19' 3"	25	13' 3"	12	29" 2"	13	28' 6"
		24	15' 7"				
27	5' 9"			11	29' 9"	12	29' 2"
24	15' 7"	27	5' 9"	10	30' 2"	11	29' 9"
21	20' 9"	26	10' 3"				
		23	17' 7"	9	30' 7"	10	30' 2"
26	10' 3"			8	30' 11"	9	30' 7"
25	13' 3"	22	19' 3"				
20	22' 1"	21	20' 9"	7	31' 3"	8	30' 11"
				6	31' 6"	7	31' 3"
19	23' 4"	20	22' 1"				
18	24' 5"	19	23' 4"	5	31' 9"	6	31' 6"
				4	31' 11"	5	31' 9"
17	25' 5"	18	24' 5"				
16	26' 4"	17	25' 5"	3	32'	4	31' 11"
				2	32' 2"	3	32'
15	27' 1"	16	26' 4"				
14	27' 10"	15	27' 1"	1	32' 2"	2	32' 2"
				0	32' 2"	1	32' 2"
Bottom of Bundle							

36' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



SWFS0023
02/14/2013 EAB

LOCATING FLOOR PLANKS NEEDED FOR 36' BIN (SPLIT)

A 36' floor is shipped in two large bundles. One bundle will contain four smaller bundles of flooring, the other will contain two.

1. Lay out these six bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 3 – one for each half of bin.
3. To find starter plank, see 36' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 30, measuring 3' 2") is starter plank. It is in bundle No. 3 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 30 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 22 (counting backward from No. 30) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.


See page 37 for important notes.

36' HAWK-CUT FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length

Top of Bundle					
9A	18' 10"	18A	16' 2"	28	13' 1"
9B	14' 10"	18B	12' 2"	29	9' 7"
8A	19' 0"	17A	16' 7"	22A	14' 1"
8B	15' 0"	17B	12' 7"	22B	10' 1"
7A	19' 2"	16A	17' 0"	21A	14' 8"
7B	15' 2"	16B	13' 0"	21B	10' 8"
6A	19' 4"	15A	17' 5"	20A	15' 3"
6B	15' 4"	15B	13' 5"	20B	11' 3"
5A	19' 5"	14A	17' 9"	19A	15' 9"
5B	15' 5"	14B	13' 9"	19B	11' 9"
4A	19' 6"	13A	18' 0"	26	17' 11"
4B	15' 6"	13B	14' 0"	27	15' 8"
3A	19' 7"	12A	18' 3"	24	21' 5"
3B	15' 7"	12B	14' 3"	25	19' 10"
2A	19' 7"	11A	18' 6"	23	22' 11"
2B	15' 7"	11B	14' 6"	0A	17' 7"
1A	19' 7"	10A	18' 8"	30	3' 2"
1B	15' 7"	10B	14' 8"		
Bottom of Bundle					

36' DIAMETER BIN – NON-SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 36' BIN (NON-SPLIT)

A 36' non-split floor is shipped in two large bundles. Each large bundle will contain two smaller bundles of flooring.


1. Lay out these four bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, see 36' Diameter Bin Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 30, measuring 6' 3") is starter plank. It is in bundle No. 1 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 30 to plank No. 1, breaking open additional bundles as needed.

See page 37 for important notes.

36' FLOOR (NON-SPLIT)

Bundle No. 1		Bundle No. 2	
Plank Number	Plank Length	Plank Number	Plank Length
<i>Top of Bundle</i>			
26	18' 6"	14	31' 7"
25	20' 4"	13	32' 2"
24	21' 11"	12	32' 8"
23	23' 4"	11	33' 2"
30	6' 3"	10	33' 6"
27	16' 5"	9	33' 10"
22	24' 7"	8	
29	10' 10"	7	34' 5"
28	14'	6	
21	25' 9"	5	34' 10"
20	26' 10"	4	
19	27' 10"	3	
18	28' 8"	2	
17	29' 6"	1	35' 2"
16	30' 3"	1	
15	31'	1	
<i>Bottom of Bundle</i>			

42' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 42' BIN (SPLIT)

A 42' floor is shipped in two large bundles. Each large bundle will contain four smaller bundles of flooring.

1. Lay out these eight bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, see 42' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 35, measuring 7' 5") is starter plank. It is in bundle No. 2 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 35 to plank No. 1, breaking open additional bundles as needed. Beginning with plank No. 30 (counting backward from No. 35) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

See page 37 for important notes.

42' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
<i>Top of Bundle</i>							
8A	22' 2"	22A	18' 4"	16A	20' 7"	30A	13' 2"
8B	18' 2"	22B	14' 4"	16B	16' 7"	30B	9' 2"
7A	22' 3"	21A	18' 9"	15A	20' 10"	29A	14' 0"
7B	18' 3"	21B	14' 9"	15B	16' 10"	29B	10' 0"
6A	22' 4"	20A	19' 2"	14A	21' 1"	28A	14' 10"
6B	18' 4"	20B	15' 2"	14B	17' 1"	28B	10' 10"
5A	22' 5"	19A	19' 7"	13A	21' 4"	27A	15' 6"
5B	18' 5"	19B	15' 7"	13B	17' 4"	27B	11' 6"
4A	22' 6"	18A	19' 11"	12A	21' 6"	26A	16' 2"
4B	18' 6"	18B	15' 11"	12B	17' 6"	26B	12' 2"
3A	22' 6"	17A	20' 3"	11A	21' 9"	25A	16' 9"
3B	18' 6"	17B	16' 3"	11B	17' 9"	25B	12' 9"
2A	22' 7"	33	15' 5"	10A	21' 10"	24A	17' 4"
2B	18' 7"	34	12' 1"	10B	17' 10"	24B	13' 4"
		35	7' 5"				
1A	20' 7"	31	20' 4"	9A	22' 0"	23A	17' 10"
1B	20' 7"	32	18' 1"	9B	18' 0"	23B	13' 10"
<i>Bottom of Bundle</i>							

LOCATING FLOOR PLANKS NEEDED FOR 42' BIN (NON-SPLIT)

A 42' floor is shipped in two large bundles. Each large bundle will contain two smaller bundles of flooring.


1. Lay out these four bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, see 42' Diameter Bin (split) - Floor and Support Layout on page 56. Plank closest to sidewall (plank No. 35, measuring 7' 5") is starter plank. It is in bundle No. 2 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 35 to plank No. 1, breaking open additional bundles as needed.

See page 37 for important notes.

42' FLOOR (NON-SPLIT)

Bundle No. 1		Bundle No. 2	
Plank Number	Plank Length	Plank Number	Plank Length
-----		-----	
Top of Bundle			
17	36' 6"	32	18' 1"
18	35' 10"	33	15' 5"
15	37' 8"	31	20' 4"
16	37' 1"	34	12' 1"
13	38' 7"	29	
14	38' 2"		
11	39' 5"	27	
12	39' 0"		
9	40' 0"	25	
10	39' 8"		
7	40' 6"	23	
8	40' 3"		
5	40' 10"	21	
6	40' 8"		
3	41' 0"	19	
4	40' 11"		
1	41' 1"	20	
2	41' 1"		
Bottom of Bundle			

48' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 48' BIN (SPLIT)

A 48' floor is shipped in two large bundles. Each large bundle will contain four smaller bundles of flooring.

1. Lay out these eight bundles of flooring.
2. Label bundles as shown below by measuring top plank of each bundle. There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, see 48' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 40, measuring 4' 6") is starter plank. It is in bundle No. 4 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 40 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 33 (counting backward from No. 40) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

See page 37 for important notes.

48' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
<i>Top of Bundle</i>							
9A	24' 11"	18A	23' 1"	27A	19' 5"	38	15' 4"
9B	20' 11"	18B	19' 1"	27B	15' 5"	39	11' 4"
						40	4' 6"
8A	25' 1"	17A	23' 5"	26A	20' 0"	32B	16' 3"
8B	21' 1"	17B	19' 5"	26B	16' 0"	33B	15' 5"
7A	25' 2"	16A	23' 8"	25A	20' 5"	31A	17' 0"
7B	21' 2"	16B	19' 8"	25B	16' 5"	31B	13' 0"
6A	25' 3"	15A	23' 10"	24A	20' 11"	30A	17' 8"
6B	21' 3"	15B	19' 10"	24B	16' 11"	30B	13' 8"
5A	25' 4"	14A	24' 1"	23A	21' 4"	29A	18' 4"
5B	21' 4"	14B	20' 1"	23B	17' 4"	29B	14' 4"
4A	25' 5"	13A	24' 3"	22A	21' 9"	28A	18' 11"
4B	21' 5"	13B	20' 3"	22B	17' 9"	28B	14' 11"
3A	25' 5"	12A	24' 6"	21A	22' 1"	36	21' 0"
3B	21' 5"	12B	20' 6"	21B	18' 1"	37	18' 5"
2A	25' 6"	11A	24' 8"	20A	22' 6"	34	25' 1"
2B	21' 6"	11B	20' 8"	20B	18' 6"	35	23' 2"
1A	25' 6"	10A	24' 10"	19A	22' 10"	0	23' 6"
1B	21' 6"	10B	20' 10"	19B	18' 10"	32A	12' 3"
						33A	11' 5"
<i>Bottom of Bundle</i>							

LOCATING FLOOR PLANKS NEEDED FOR 48' BIN (NON-SPLIT)

A 48' floor is shipped in two large bundles. Each large bundle will contain two smaller bundles of flooring.


1. Lay out these four bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.**
3. To find starter plank, see 48' Diameter Bin (split) - Floor and Support Layout on page 59. Plank closest to sidewall (plank No. 40, measuring 4' 4") is starter plank. It is in bundle No. 3 or 4 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 40 to plank No. 0, breaking open additional bundles as needed.

See page 37 for important notes.

48' FLOOR (NON-SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
Top of Bundle							
18	42' 3"	19	41' 8"	40	4' 4"	39	11' 2"
19	41' 8"	20	41' 0"	38	15' 2"	40	4' 4"
16	43' 5"	17	42' 10"	39	11' 2"	37	18' 3"
17	42' 10"	18	42' 3"	36	20' 10"	38	15' 2"
14	44' 3"	15	43' 10"	37	18' 3"	35	23' 1"
15	43' 10"	16	43' 5"	34	25' 1"	36	20' 10"
12	45' 1"	13	44' 8"	35	23' 1"	33	26' 10"
13	44' 8"	14	44' 3"	32	28' 6"	34	25' 1"
10	45' 8"	11	45' 5"	33	26' 10"	31	30' 0"
11	45' 5"	12	45' 1"	30	31' 4"	32	28' 6"
8	46' 2"	9	46' 0"	31	30' 0"	29	32' 8"
9	46' 0"	10	45' 8"	28	33' 10"	30	31' 4"
6	46' 7"	7	46' 5"	29	32' 8"	27	34' 11"
7	46' 5"	8	46' 2"	26	36' 0"	28	33' 10"
4	46' 10"	5	46' 9"	27	34' 11"	25	36' 11"
5	46' 9"	6	46' 7"	24	37' 10"	26	36' 0"
2	47' 0"	3	46' 11"	25	36' 11"	23	38' 9"
3	46' 11"	4	46' 10"	22	39' 6"	24	37' 10"
0	47' 0"	1	47' 0"	23	38' 9"	21	40' 3"
1	47' 0"	2	47' 0"	20	41' 0"	22	39' 6"
Bottom of Bundle							
				21	40' 3"		

54' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 54' BIN (SPLIT)

A 54' floor is shipped in two large bundles. Each large bundle will contain four smaller bundles of flooring.


1. Lay out these eight bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin.
3. To find starter plank, look at 54' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 45, measuring 11' 0") is starter plank. It is in bundle No. 4 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 45 to plank No. 1, breaking open additional bundles as needed. Beginning with plank No. 39 (counting backward from No. 45) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

54' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
<i>Top of Bundle</i>							
11A	27' 11"	22A	25' 6"	32A	21' 3"	44	15' 6"
11B	23' 11"	22B	21' 6"	32B	17' 3"	45	11' 0"
10A	28' 0"	21A	25' 10"	31A	21' 9"	39A	16' 2"
10B	24' 0"	21B	21' 10"	31B	17' 9"	39B	12' 2"
9A	28' 2"	20A	26' 1"	30A	22' 3"	38A	17' 1"
9B	24' 2"	20B	22' 1"	30B	18' 3"	38B	13' 1"
8A	28' 3"	19A	26' 4"	29A	22' 9"	37A	17' 10"
8B	24' 3"	19B	22' 4"	29B	18' 9"	37B	13' 10"
7A	28' 4"	18A	26' 7"	28A	23' 3"	36A	18' 8"
7B	24' 4"	18B	22' 7"	28B	19' 3"	36B	14' 8"
6A	28' 5"	17A	26' 10"	27A	23' 8"	35A	19' 4"
6B	24' 5"	17B	22' 10"	27B	19' 8"	35B	15' 4"
5A	28' 5"	16A	27' 1"	26A	24' 1"	34A	20' 0"
5B	24' 5"	16B	23' 1"	26B	20' 1"	34B	16' 0"
4A	28' 6"	15A	27' 3"	25A	24' 6"	33A	20' 8"
4B	24' 6"	15B	23' 3"	25B	20' 6"	33B	16' 8"
3A	28' 6"	14A	27' 5"	24A	24' 10"	42	21' 10"
3B	24' 6"	14B	23' 5"	24B	20' 10"	43	19' 0"
2A	28' 7"	13A	27' 7"	23A	25' 3"	40	26' 5"
2B	24' 7"	13B	23' 7"	23B	21' 3"	41	24' 4"
1A	26' 7"	12A	27' 9"				
1B	26' 7"	12B	23' 9"				
<i>Bottom of Bundle</i>							

See page 37 for important notes.

60' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 60' BIN (SPLIT)

A 60' floor is shipped in three large bundles. Two of these large bundles will contain four smaller bundles of flooring, and one bundle will contain two smaller bundles.

1. Lay out these 10 bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 4 – one for each half of bin. Label remaining two bundles No. 5 and No. 6 according to plank lengths below.
3. To find starter plank, see 60' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 50, measuring 7' 0") is starter plank. It is in bundle No. 6 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 50 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 42 (counting backward from No. 50) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.


60' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4		Bundle No. 5		Bundle No. 6	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
Top of Bundle											
10A	30' 11"	20A	29' 2"	30A	25' 9"	40A	19' 11"	42B	14' 3"	41B	15' 3"
10B	26' 11"	20B	25' 2"	30B	21' 9"	40B	15' 11"	42B	14' 3"	41B	15' 3"
9A	31' 1"	19A	29' 5"	29A	26' 2"	39A	20' 8"	42A	18' 3"	48	17' 9"
9B	27' 1"	19B	25' 5"	29B	22' 2"	39B	16' 8"	42A	18' 3"	48	17' 9"
8A	31' 2"	18A	29' 8"	28A	26' 7"	38A	21' 5"	41A	19' 2"	47	21' 1"
8B	27' 2"	18B	25' 8"	28B	22' 7"	38B	17' 5"	41A	19' 2"	49	13' 5"
										50	7' 0"
7A	31' 2"	17A	29' 10"	27A	27' 0"	37A	22' 1"	47	21' 1"	46	23' 11"
7B	27' 2"	17B	25' 10"	27B	23' 0"	37B	18' 1"	49	13' 5"	46	23' 11"
								50	7' 0"	46	23' 11"
6A	31' 3"	16A	30' 1"	26A	27' 4"	36A	22' 8"			45	26' 5"
6B	27' 3"	16B	26' 1"	26B	23' 4"	36B	18' 8"	44	28' 4"	45	26' 5"
								44	28' 4"	45	26' 5"
5A	31' 4"	15A	30' 3"	25A	27' 8"	35A	23' 3"				
5B	27' 4"	15B	26' 3"	25B	23' 8"	35B	19' 3"	0A	29' 6"	43	30' 8"
								0B	29' 6"	43	30' 8"
4A	31' 5"	14A	30' 5"	24A	28' 0"	34A	23' 10"				
4B	27' 5"	14B	26' 5"	24B	24' 0"	34B	19' 10"				
3A	31' 5"	13A	30' 7"	23A	28' 4"	33A	24' 4"				
3B	27' 5"	13B	26' 7"	23B	24' 4"	33B	20' 4"				
2A	31' 6"	12A	30' 8"	22A	28' 8"	32A	24' 10"				
2B	27' 6"	12B	26' 8"	22B	24' 8"	32B	20' 10"				
1A	31' 6"	11A	30' 10"	21A	28' 11"	31A	25' 4"				
1B	27' 6"	11B	26' 10"	21B	24' 11"	31B	21' 4"				

Bottom of Bundle

See page 37 for important notes.

72' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 72' BIN (SPLIT)

A 72' floor is shipped in six large bundles. Each large bundle will contain two smaller bundles of flooring.


1. Lay out these 12 bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 6—one for each half of bin.
3. To find starter plank, see 72' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 61, measuring 4' 11") is starter plank. It is in bundle No. 6 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 61 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 51 (counting backward from No. 61) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

72' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4		Bundle No. 5		Bundle No. 6	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
-----		-----		-----		-----		-----		-----	
Top of Bundle											
10A	33' 3"	20A	31' 10"	30A	29' 3"	40A	25' 1"	48A	20' 2"	59	18' 10"
10B	37' 3"	20B	35' 10"	30B	33' 3"	40B	29' 1"	48B	24' 2"	60	13' 10"
										61	4' 11"
9A	33' 4"	19A	32' 0"	29A	29' 7"	39A	25' 7"	47A	20' 11"	51A	17' 9"
9B	37' 4"	19B	36' 0"	29B	33' 7"	39B	29' 7"	47B	24' 11"	51B	21' 9"
8A	33' 5"	18A	32' 2"	28A	29' 10"	38A	26' 0"	46A	21' 7"	50A	18' 7"
8B	37' 5"	18B	36' 2"	28B	33' 10"	38B	30' 0"	46B	25' 7"	50B	22' 7"
7A	33' 6"	17A	32' 4"	27A	30' 2"	37A	26' 6"	45A	22' 3"	49A	19' 5"
7B	37' 6"	17B	36' 4"	27B	34' 2"	37B	30' 6"	45B	26' 3"	49B	23' 5"
6A	33' 7"	16A	32' 6"	26A	30' 5"	36A	26' 11"	44A	22' 10"	57	25' 11"
6B	37' 7"	16B	36' 6"	26B	34' 5"	36B	30' 11"	44B	26' 10"	58	22' 8"
5A	33' 7"	15A	32' 8"	25A	30' 8"	35A	27' 4"	43A	23' 5"	55	31' 4"
5B	37' 7"	15B	36' 8"	25B	34' 8"	35B	31' 4"	43B	27' 5"	56	28' 10"
4A	33' 8"	14A	32' 10"	24A	30' 11"	34A	27' 9"	42A	24' 0"	53	35' 8"
4B	37' 8"	14B	36' 10"	24B	34' 11"	34B	31' 9"	42B	28' 0"	54	33' 7"
3A	33' 8"	13A	32' 11"	23A	31' 2"	33A	28' 2"	41A	24' 7"	52	37' 8"
3B	37' 8"	13B	36' 11"	23B	35' 2"	33B	32' 2"	41B	28' 7"	0A	35' 8"
2A	33' 8"	12A	33' 1"	22A	31' 5"	32A	28' 6"				
2B	37' 8"	12B	37' 1"	22B	35' 5"	32B	32' 6"				
1A	35' 8"	11A	33' 2"	21A	31' 7"	31A	28' 11"				
1B	35' 8"	11B	37' 2"	21B	35' 7"	31B	32' 11"				
Bottom of Bundle											

See page 37 for important notes.

75' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 75' BIN (SPLIT)

A 75' floor is shipped in six large bundles. Each large bundle will contain two smaller bundles of flooring.


1. Lay out these 12 bundles of flooring.
2. **Label bundles as shown below by measuring top plank of each bundle.** There will be two bundles the same length for bundles 1 through 6 – one for each half of bin.
3. To find starter plank, see 75' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 63, measuring 8' 1") is starter plank. It is in bundle No. 6 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 63 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 54 (counting backward from No. 63) there are planks A and B. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

75' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4		Bundle No. 5		Bundle No. 6	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
-----		-----		-----		-----		-----		-----	
Top of Bundle											
10A	34' 7"	20A	33' 2"	30A	30' 9"	40A	26' 9"	50A	20' 9"	62	15' 5"
10B	38' 7"	20B	37' 2"	30B	34' 9"	40B	30' 9"	50B	24' 9"	63	8' 1"
9A	34' 8"	19A	33' 5"	29A	31' 0"	39A	27' 3"	49A	21' 6"	54A	17' 5"
9B	38' 8"	19B	37' 5"	29B	35' 0"	39B	31' 3"	49B	25' 6"	54B	21' 5"
8A	34' 9"	18A	33' 7"	28A	31' 4"	38A	27' 8"	48A	22' 2"	53A	18' 4"
8B	38' 9"	18B	37' 7"	28B	35' 4"	38B	31' 8"	48B	26' 2"	53B	22' 4"
7A	34' 10"	17A	33' 9"	27A	31' 7"	37A	28' 1"	47A	22' 10"	52A	19' 2"
7B	38' 10"	17B	37' 9"	27B	35' 7"	37B	32' 1"	47B	26' 10"	52B	23' 2"
6A	34' 10"	16A	33' 10"	26A	31' 10"	36A	28' 6"	46A	23' 6"	51A	20' 0"
6B	38' 10"	16B	37' 10"	26B	35' 10"	36B	32' 6"	46B	27' 6"	51B	24' 0"
5A	34' 11"	15A	34' 0"	25A	32' 1"	35A	28' 11"	45A	24' 1"	60	23' 11"
5B	38' 11"	15B	38' 0"	25B	36' 1"	35B	32' 11"	45B	28' 1"	61	20' 1"
4A	34' 11"	14A	34' 2"	24A	32' 4"	34A	29' 4"	44A	24' 8"	58	29' 11"
4B	38' 11"	14B	38' 2"	24B	36' 4"	34B	33' 4"	44B	28' 8"	59	27' 1"
3A	35' 0"	13A	34' 3"	23A	32' 7"	33A	29' 8"	43A	25' 3"	56	34' 10"
3B	39' 0"	13B	38' 3"	23B	36' 7"	33B	33' 8"	43B	29' 3"	57	32' 6"
2A	35' 0"	12A	34' 5"	22A	32' 9"	32A	30' 1"	42A	25' 9"	55	36' 11"
2B	39' 0"	12B	38' 5"	22B	36' 9"	32B	34' 1"	42B	29' 9"	0A	37' 0"
1A	37' 0"	11A	34' 6"	21A	33' 0"	31A	30' 5"	41A	26' 3"		
1B	37' 0"	11B	38' 6"	21B	37' 0"	31B	34' 5"	41B	30' 3"		
Bottom of Bundle											

See page 37 for important notes.

78' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 78' BIN (SPLIT)

A 78' floor is shipped in five large bundles. Three of these bundles will contain four smaller bundles of flooring, one large bundle will contain two smaller bundles, and one large bundle will contain three smaller bundles.

1. Lay out these 17 bundles of flooring.
2. **Label bundles as shown below and on next page by measuring top plank of each bundle.** Bundle Nos. 1 through 8 will each have two bundles the same length – one for each half of bin. Label the remaining bundle No. 9, corresponding with top plank length listed on next page.
3. To find starter plank, see 78' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 66, measuring 7' 2") is starter plank. It is in bundle No. 9 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 66 to plank No. 0, breaking open additional bundles as needed. Beginning with plank No. 58 (counting backward from No. 66) there are planks A and B, and beginning with plank No. 31 there are planks A, B and C. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

78' FLOOR (SPLIT)

Bundle No. 1		Bundle No. 2		Bundle No. 3		Bundle No. 4		Bundle No. 5	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
-----		-----		-----		-----		-----	
Top of Bundle									
6A	21' 8"	12A	21' 5"	18A	20' 10"	24A	20' 1"	30A	19' 2"
6B	27' 9"	12B	27' 5"	18B	26' 11"	24B	26' 2"	30B	25' 2"
6C	27' 9"	12C	27' 6"	18C	26' 11"	24C	26' 2"	30C	25' 1"
5A	25' 10"	11A	25' 6"	17A	25' 0"	23A	24' 4"	29A	23' 4"
5B	25' 9"	11B	25' 6"	17B	25' 0"	23B	24' 4"	29B	23' 4"
5C	25' 9"	11C	25' 6"	17C	25' 0"	23C	24' 3"	29C	23' 3"
4A	21' 9"	10A	21' 6"	16A	21' 2"	22A	20' 6"	28A	19' 6"
4B	27' 10"	10B	27' 7"	16B	27' 1"	22B	26' 5"	28B	25' 6"
4C	27' 10"	10C	27' 7"	16C	27' 1"	22C	26' 5"	28C	25' 6"
3A	25' 10"	9A	25' 8"	15A	25' 2"	21A	24' 7"	27A	23' 8"
3B	25' 10"	9B	25' 7"	15B	25' 2"	21B	24' 7"	27B	23' 8"
3C	25' 9"	9C	25' 7"	15C	25' 3"	21C	24' 6"	27C	23' 8"
2A	21' 10"	8A	27' 8"	14A	21' 4"	20A	20' 8"	26A	19' 10"
2B	27' 10"	8B	27' 8"	14B	27' 3"	20B	26' 8"	26B	25' 10"
2C	27' 10"	8C	21' 8"	14C	27' 3"	20C	26' 8"	26C	25' 10"
1A	25' 10"	7A	25' 9"	13A	25' 5"	19A	24' 10"	25A	24' 0"
1B	25' 10"	7B	25' 8"	13B	25' 5"	19B	24' 10"	25B	24' 0"
1C	25' 10"	7C	25' 8"	13C	25' 4"	19C	24' 9"	25C	24' 0"
Bottom of Bundle									

See next page for Bundles 6-9

See page 37 for important notes.


LOCATING FLOOR PLANKS NEEDED FOR 78' BIN (SPLIT)

78' FLOOR (SPLIT)

Bundle No. 6		Bundle No. 7		Bundle No. 8		Bundle No. 9	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
Top of Bundle							
38A	33' 10"	47A	29' 4"	57A	21' 9"	65	15' 2"
38B	29' 10"	47B	25' 4"	57B	17' 9"	65	15' 2"
37A	34' 2"	46A	29' 11"	56A	22' 9"	58A	20' 9"
37B	30' 2"	46B	25' 11"	56B	18' 9"	58B	16' 9"
36A	34' 7"	45A	30' 6"	55A	23' 8"	58A	20' 9"
36B	30' 7"	45B	26' 6"	55B	19' 8"	58B	16' 9"
35A	34' 11"	44A	31' 0"	54A	24' 6"	63	24' 1"
35B	30' 11"	44B	27' 0"	54B	20' 6"	63	24' 1"
34A	35' 4"	43A	31' 6"	53A	25' 3"	0	25' 10"
34B	31' 4"	43B	27' 6"	53B	21' 3"	66	7' 2"
						66	7' 2"
33A	35' 8"	42A	32' 0"	52A	26' 0"		
33B	31' 8"	42B	28' 0"	52B	22' 0"	0	25' 10"
						0	25' 10"
32A	36' 0"	41A	32' 6"	51A	26' 9"		
32B	32' 0"	41B	28' 6"	51B	22' 9"	62	27' 6"
						62	27' 6"
31A	22' 11"	40A	32' 11"	50A	27' 5"		
31B	22' 11"	40B	28' 11"	50B	23' 5"	61	30' 5"
						61	30' 5"
31C	23' 0"	39A	33' 4"	49A	28' 1"		
64	20' 2"	39B	29' 4"	49B	24' 1"	60	33' 0"
						60	33' 0"
				48A	28' 9"		
				48B	24' 9"	59	35' 5"
						59	35' 5"
Bottom of Bundle							

See page 37 for important notes.

90' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 90' BIN (SPLIT)

A 90' floor is shipped in six large bundles. Five of those bundles will contain four smaller bundles of flooring and one large bundle will contain three smaller bundles.

1. Lay out these 23 bundles of flooring.
2. Label bundles as shown below and on next page by measuring top plank of each bundle. There will be two bundles the same length for numbers 1 through 11, and 13 through 23 – one for each half of bin. Label remaining bundle No. 12.
3. To find starter plank, see 90' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 77, measuring 3' 10") is starter plank. It is in bundle No. 12 and is shortest plank in bundle.
4. Lay out remaining planks. Work in descending order from plank No. 77 to plank No. 1, breaking open additional bundles as needed. Beginning with plank No. 72 (counting backward from No. 77) there are planks A and B, and beginning with plank No. 56 there are planks A, B and C. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

90' FLOOR (SPLIT)

Bundles 1 & 23		Bundles 2 & 22		Bundles 3 & 21		Bundles 4 & 20		Bundles 5 & 19		Bundles 6 & 18	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
-----		-----		-----		-----		-----		-----	
Top of Bundle											
6A	25' 9"	12A	25' 6"	18A	25' 1"	24A	24' 5"	30A	23' 7"	36A	22' 5"
6B	31' 10"	12B	31' 6"	18B	31' 1"	24B	30' 5"	30B	29' 7"	36B	28' 6"
6C	29' 9"	12C	31' 6"	18C	31' 1"	24C	30' 5"	30C	29' 7"	36C	28' 6"
5A	31' 10"	11A	29' 6"	17A	29' 2"	23A	28' 6"	29A	27' 9"	35A	26' 8"
5B	29' 9"	11B	29' 6"	17B	29' 2"	23B	28' 6"	29B	27' 9"	35B	26' 8"
5C	29' 9"	11C	29' 6"	17C	29' 2"	23C	28' 6"	29C	27' 9"	35C	26' 8"
4A	25' 9"	10A	25' 7"	16A	25' 3"	22A	24' 8"	28A	23' 11"	34A	22' 10"
4B	31' 10"	10B	31' 7"	16B	31' 3"	22B	30' 9"	28B	29' 11"	34B	28' 11"
4C	29' 10"	10C	31' 7"	16C	31' 3"	22C	30' 9"	28C	29' 11"	34C	28' 11"
3A	31' 10"	9A	29' 8"	15A	29' 3"	21A	28' 9"	27A	28' 0"	33A	27' 1"
3B	29' 10"	9B	29' 8"	15B	29' 3"	21B	28' 9"	27B	28' 0"	33B	27' 1"
3C	29' 10"	9C	29' 8"	15C	29' 3"	21C	28' 9"	27C	28' 0"	33C	27' 1"
2A	31' 10"	8A	25' 8"	14A	25' 4"	20A	24' 10"	26A	24' 2"	32A	23' 3"
2B	31' 10"	8B	31' 9"	14B	31' 5"	20B	30' 11"	26B	30' 3"	32B	29' 4"
2C	25' 10"	8C	31' 9"	14C	31' 5"	20C	30' 11"	26C	30' 3"	32C	29' 4"
1A	29' 10"	7A	29' 9"	13A	29' 5"	19A	29' 0"	25A	28' 3"	31A	27' 5"
1B	29' 10"	7B	29' 9"	13B	29' 5"	19B	29' 0"	25B	28' 3"	31B	27' 5"
1C	29' 10"	7C	29' 9"	13C	29' 5"	19C	29' 0"	25C	28' 3"	31C	27' 5"

Bottom of Bundle

See next page for Bundles 7-17

See page 37 for important notes.

LOCATING FLOOR PLANKS NEEDED FOR 90' BIN (SPLIT)


90' FLOOR (SPLIT)

Bundles 7 & 17		Bundles 8 & 16		Bundles 9 & 15		Bundles 10 & 14		Bundles 11 & 13		Bundle 12	
Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length	Plank Number	Plank Length
-----		-----		-----		-----		-----		-----	
Top of Bundle											
42A	21' 1"	48A	19' 5"	54A	17' 4"	62A	24' 8"	56C	22' 7"	72A	14' 0"
42B	27' 2"	48B	25' 5"	54B	23' 5"	62B	28' 8"	55A	21' 0"	72B	18' 0"
42C	27' 2"	48C	25' 5"	54C	23' 5"	61A	25' 5"	55B	21' 0"	77	3' 10"
41A	25' 4"	47A	23' 9"	53A	21' 9"	61B	29' 6"	55C	21' 0"	76	14' 8"
41B	25' 4"	47B	23' 9"	53B	21' 9"	60A	26' 2"	71A	15' 5"	75	20' 6"
41C	25' 4"	47C	23' 9"	53C	21' 9"	60B	30' 3"	71B	19' 6"	56A	16' 6"
40A	21' 7"	46A	20' 0"	52A	18' 1"	59A	26' 11"	70A	16' 9"	56B	22' 7"
40B	27' 7"	46B	26' 1"	52B	24' 2"	59B	30' 11"	70B	20' 10"	72A	14' 0"
40C	27' 7"	46C	26' 1"	52C	24' 2"	58A	27' 7"	69A	18' 0"	72B	18' 0"
39A	25' 10"	45A	24' 3"	51A	22' 5"	58B	31' 7"	69B	22' 0"	77	3' 10"
39B	25' 10"	45B	24' 3"	51B	22' 5"	57A	32' 3"	68A	19' 1"	76	14' 8"
39C	25' 10"	45C	24' 3"	51C	22' 5"	57B	28' 3"	68B	23' 2"	75	20' 6"
38A	28' 1"	44A	20' 7"	50A	18' 9"	64A	23' 0"	67A	20' 2"	56A	16' 6"
38B	28' 1"	44B	26' 7"	50B	24' 10"	64B	27' 1"	67B	24' 3"	56B	22' 7"
38C	22' 1"	44C	26' 7"	50C	24' 10"	63A	23' 10"	66A	21' 2"		
37A	26' 3"	43A	24' 10"	49A	23' 1"	63B	27' 11"	66B	25' 3"		
37B	26' 3"	43B	24' 10"	49B	23' 1"	74	25' 0"	65A	22' 1"		
37C	26' 3"	43C	24' 10"	49C	23' 1"	73	28' 9"	65B	26' 2"		

Bottom of Bundle

See page 37 for important notes.

105' DIAMETER BIN – SPLIT FLOOR AND SUPPORT LAYOUT



LOCATING FLOOR PLANKS NEEDED FOR 105' BIN (SPLIT)

A 105' floor is shipped in 14 large bundles. Twelve of these large bundles will contain two smaller bundles of flooring and two of the large bundles will contain one smaller bundle.

1. Lay out these 26 bundles of flooring.
2. **Label bundles as shown below and on next page by measuring top plank of each bundle.** There will be two bundles the same length for numbers 1 through 10, 12, 13, and 15 through 26 – one for each half of bin. Label the two remaining bundles No. 11 and No. 14, corresponding to the plank lengths shown on next page.
3. To find starter plank, see 105' Diameter Bin (split) - Floor and Support Layout on previous page. Plank closest to sidewall (plank No. 89, measuring 10' 6") is starter plank. It is the shortest plank in bundle No. 14. There is one for each side of bin.
4. Lay out remaining planks. Work in descending order from plank No. 89 to plank No. 1, breaking open additional bundles as needed. Beginning with plank No. 82 (counting backward from No. 89) there are planks A and B, and beginning with plank No. 63 there are planks A, B and C. These are planks that have been split. Alternate between longer and shorter planks to keep seams offset from seams in adjacent planks (as shown in layout drawing).
5. Complete installation by following applicable floor support instructions as well as splicing instructions on page 34.

105' FLOOR (SPLIT)

Bundles 1 & 26		Bundles 2 & 25		Bundles 3 & 24		Bundles 4 & 23		Bundles 5 & 22		Bundles 6 & 21		Bundles 7 & 20	
Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length
Top of Bundle													
6A	34' 7"	12A	34' 5"	18A	34' 0"	24A	33' 3"	30A	32' 7"	36A	32' 0"	42A	30' 4"
6B	34' 8"	12B	34' 4"	18B	34' 0"	24B	34' 0"	30B	33' 0"	36B	31' 9"	42B	31' 6"
6C	34' 7"	12C	34' 4"	18C	34' 0"	24C	33' 3"	30C	32' 7"	36C	31' 9"	42C	30' 4"
5A	34' 8"	11A	34' 6"	17A	34' 2"	23A	34' 0"	29A	33' 0"	35A	32' 0"	41A	31' 8"
5B	34' 7"	11B	34' 5"	17B	34' 0"	23B	33' 4"	29B	32' 9"	35B	32' 0"	41B	30' 7"
5C	34' 7"	11C	34' 6"	17C	34' 0"	23C	33' 4"	29C	32' 9"	35C	32' 0"	41C	30' 7"
4A	34' 7"	10A	34' 6"	16A	34' 1"	22A	33' 6"	28A	33' 0"	34A	32' 0"	40A	31' 0"
4B	34' 9"	10B	34' 6"	16B	34' 3"	22B	34' 0"	28B	33' 0"	34B	32' 6"	40B	31' 5"
4C	34' 7"	10C	34' 5"	16C	34' 1"	22C	33' 6"	28C	33' 0"	34C	32' 0"	40C	31' 0"
3A	34' 9"	9A	34' 6"	15A	34' 3"	21A	34' 0"	27A	33' 5"	33A	32' 7"	39A	31' 11"
3B	34' 7"	9B	34' 6"	15B	34' 2"	21B	33' 7"	27B	33' 0"	33B	32' 2"	39B	31' 0"
3C	34' 7"	9C	34' 6"	15C	34' 2"	21C	33' 7"	27C	33' 0"	33C	32' 2"	39C	31' 0"
2A	34' 7"	8A	34' 6"	14A	34' 4"	20A	33' 9"	26A	33' 0"	32A	32' 3"	38A	31' 3"
2B	34' 9"	8B	34' 7"	14B	34' 3"	20B	34' 0"	26B	33' 8"	32B	33' 0"	38B	32' 0"
2C	34' 7"	8C	34' 6"	14C	34' 3"	20C	33' 9"	26C	33' 0"	32C	32' 3"	38C	31' 3"
1A	34' 9"	7A	34' 8"	13A	34' 4"	19A	34' 0"	25A	34' 0"	31A	33' 0"	37A	32' 0"
1B	34' 7"	7B	34' 6"	13B	34' 4"	19B	33' 11"	25B	33' 0"	31B	32' 5"	37B	31' 6"
1C	34' 7"	7C	34' 6"	13C	34' 4"	19C	33' 11"	25C	33' 0"	31C	32' 5"	37C	31' 6"

Bottom of Bundle

**See next page for Bundles 8-19
See page 37 for important notes.**

LOCATING FLOOR PLANKS NEEDED FOR 105' BIN (SPLIT)

105' FLOOR (SPLIT)

Bundles 8 & 19		Bundles 9 & 18		Bundles 10 & 17		Bundle 11		Bundles 12 & 16		Bundles 13 & 15		Bundle 14	
Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length	Plank #	Plank Length
Top of Bundle													
48A	29' 0"	54A	28' 0"	60A	26' 1"	63A	24' 6"	72A	32' 11"	81A	24' 1"	89	10' 6"
48B	30' 0"	54B	27' 7"	60B	25' 8"	63B	24' 6"	72B	28' 11"	81B	20' 1"	89	10' 6"
48C	29' 0"	54C	27' 7"	60C	25' 8"	63C	24' 6"	71A	33' 8"	80A	25' 4"	88	18' 8"
47A	30' 0"	53A	28' 1"	59A	26' 5"	63A	25' 1"	71B	29' 8"	80B	21' 4"	88	18' 8"
47B	29' 5"	53B	28' 0"	59B	26' 0"	63B	25' 1"	70A	34' 5"	79A	26' 5"	82A	22' 10"
47C	29' 5"	53C	28' 0"	59C	26' 0"	63C	24' 6"	70B	30' 5"	79B	22' 5"	82B	18' 10"
46A	30' 0"	52A	28' 0"	58A	26' 3"	62A	25' 2"	69A	35' 2"	78A	27' 6"	82A	22' 10"
46B	29' 9"	52B	28' 11"	58B	27' 0"	62B	25' 0"	69B	31' 2"	78B	23' 6"	82B	18' 10"
46C	29' 9"	52C	28' 0"	58C	26' 3"	62C	25' 0"	68A	35' 10"	77A	28' 6"	87	24' 4"
45A	30' 4"	51A	29' 10"	57A	27' 1"	61A	26' 0"	68B	31' 10"	77B	24' 6"	87	24' 4"
45B	30' 0"	51B	28' 4"	57B	26' 6"	61B	25' 2"	67A	36' 6"	76A	29' 6"	86	28' 8"
45C	30' 0"	51C	28' 4"	57C	26' 6"	61C	25' 2"	67B	32' 6"	76B	25' 6"	86	28' 8"
44A	30' 0"	50A	29' 0"	56A	27' 0"	62A	25' 2"	66A	37' 2"	75A	30' 5"	85	32' 6"
44B	30' 11"	50B	28' 9"	56B	27' 5"	62B	25' 0"	66B	33' 2"	75B	26' 5"	85	32' 6"
44C	30' 0"	50C	28' 9"	56C	27' 0"	62C	25' 0"	65A	37' 10"	74A	31' 3"	84	35' 11"
43A	31' 3"	49A	29' 4"	55A	28' 0"	61A	26' 0"	65B	33' 10"	74B	27' 3"	84	35' 11"
43B	30' 2"	49B	29' 0"	55B	27' 2"	61B	25' 2"	64A	38' 5"	73A	32' 1"	83	38' 11"
43C	30' 2"	49C	29' 0"	55C	27' 2"	61C	25' 2"	64B	34' 5"	73B	28' 1"	83	38' 11"
Bottom of Bundle													

See page 37 for important notes.



CONTACT INFORMATION

Owner's manuals are available from Sukup and additional copies can be requested at address, phone number, or e-mail address shown below. Please indicate manual number L1417 when requesting the *Channel-Lok* Bin Floors & Supports Owner's Installation Manual for major bin diameters.

SUKUP DEALER INFORMATION

Dealer name: _____
Address: _____
Cell phone: _____
Office phone: _____
Fax: _____

EMERGENCIES – KNOW WHAT TO DO

Have emergency numbers and written directions to your location near your telephone in case of emergency. Spaces for emergency phone numbers to be recorded have been provided below.

Ambulance • Fire • Police: 9-1-1
Bin rescue team: _____
Emergency medical squad: _____
Address of work site: _____
Directions to work site: _____



Sukup Manufacturing Co.

1555 255th Street, Box 677

Sheffield, Iowa, USA 50475-0677

Phone: 641-892-4222

Fax: 641-892-4629

Website: www.sukup.com

Email: info@sukup.com